


KHA152KP51DHCZA Obsolete KHA, Ceramic, 1500 pF, 10%, 2000 VDC, X7R, Lead Spacing = 7.5mm



General Information		
Series	КНА	
Style	Radial Disc	
RoHS	Yes	
Termination	Tin	
Failure Rate	N/A	
AEC-Q200	No	
Miscellaneous	Climate Category: 55/125/21.	

Specifications		
Capacitance	1500 pF	
Capacitance Tolerance	10%	
Voltage DC	2000 VDC	
Dielectric Withstanding Voltage	4000 VDC	
Temperature Range	-55/+125°C	
Temperature Coefficient	X7R	
Dissipation Factor	2.5%	
Insulation Resistance	10 GOhms	
Insulation Resistance	10 GOhms	

Dimensions	
D	12.5mm MAX
т	4.5mm MAX
S	7.5mm NOM
F	0.6mm +/-0.1mm

Packaging Specifications		
Packaging	T&R, 360mm, H0 = 16mm, Component Pitch = 25.4mm	
Packaging Quantity	500	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.