



SENTRON, Molded case switch 3LD5 UL, Main switch, 3-pole, certified according to UL489 UL60947-4-1 and IEC60947-3, UL: 125A, SCCR 65kA at 480VAC, Operating power at 480VAC 3-phase: 75hp, IEC: 125A, Operating power at AC-23A at 400V: 55kW, front-mounted, rotary operating mechanism, black, 4-hole mounting of the handle, incl. terminal covers for the infeed side

| Model  |                                   |
|--|-----------------------------------|
| product brand name   | SENTRON                           |
| product designation  | 3LD UL switch disconnecter        |
| design of the product  | Main switch                       |
| display version / for switch position indicator manual operation   | 1 ON - 0 OFF                      |
| design of the actuating element  | selector switch                   |
| design of handle   | rotary operating mechanism, black |
| type of the driving mechanism / motor drive  | No                                |
| General technical data   |                                   |
| number of poles  | 3                                 |
| type of device   | fixed mounting                    |
| type of switch   | front mounted                     |
| size of switch disconnecter  | 3                                 |
| mechanical service life (switching cycles) / typical   | 100 000                           |
| electrical endurance (switching cycles)  |                                   |
| • at AC-23 A / at 690 V  | 6 000                             |
| I <sub>2t</sub> value / with closed switch / at 690 V / for combination switch + gG fuse / maximum             | 223 kA <sub>2</sub> .s            |
| let-through I <sub>2t</sub> value / with closed switch / at 440 V / for combination switch + gG fuse / maximum | 223 kA <sub>2</sub> .s            |
| operating frequency / maximum  | 50 1/h                            |
| Voltage  |                                   |
| insulation voltage / rated value   | 690 V                             |
| surge voltage resistance / rated value   | 6 kV                              |
| Protection class   |                                   |
| protection class IP  | IP65                              |
| degree of protection NEMA rating   | 1, 3R, 4X, 12                     |
| protection class IP / on the front   | IP65                              |
| Dissipation  |                                   |
| power loss [W]   |                                   |
| • for rated value of the current / at AC / in hot operating state / per pole                                   | 36 W                              |
| • per conductor / typical  | 36 W                              |
| Current  |                                   |
| operational current  |                                   |
| • at 40 °C / rated value   | 125 A                             |
| • at 45 °C / rated value   | 125 A                             |
| • at 50 °C / rated value   | 125 A                             |
| • at 55 °C / rated value   | 125 A                             |

|   |        |
|---|--------|
| <ul style="list-style-type: none"> <li>• at AC / rated value</li> </ul>   | 125 A  |
| <ul style="list-style-type: none"> <li>• at AC-23 A / at 400 V / rated value</li> </ul>                               | 125 A  |
| <ul style="list-style-type: none"> <li>• at AC-21 / at 690 V / rated value</li> </ul>                                 | 125 A  |
| <ul style="list-style-type: none"> <li>• at AC-21 A / at 240 V / rated value</li> </ul>                               | 125 A  |
| <ul style="list-style-type: none"> <li>• at AC-21 A / at 440 V / rated value</li> </ul>                               | 125 A  |
| operational current / of upstream fuse / rated value  | 125 A  |
| let-through current / with closed switch  |        |
| <ul style="list-style-type: none"> <li>• at 440 V / for combination switch + gG fuse / maximum</li> </ul>             | 16 kA  |
| <ul style="list-style-type: none"> <li>• at 690 V / for combination switch + gG fuse / maximum permissible</li> </ul> | 15 kA  |
| <b>Main circuit</b>   |        |
| operating power   |        |
| <ul style="list-style-type: none"> <li>• at AC-23 A / at 240 V / rated value</li> </ul>                               | 37 kW  |
| <ul style="list-style-type: none"> <li>• at AC-23 A / at 440 V / rated value</li> </ul>                               | 55 kW  |
| <ul style="list-style-type: none"> <li>• at AC-23 A / at 690 V / rated value</li> </ul>                               | 45 kW  |
| <ul style="list-style-type: none"> <li>• at AC-3 / at 240 V / rated value</li> </ul>                                  | 37 kW  |
| <ul style="list-style-type: none"> <li>• at AC-3 / at 400 V / rated value</li> </ul>                                  | 55 kW  |
| <ul style="list-style-type: none"> <li>• at AC-3 / at 690 V / rated value</li> </ul>                                  | 37 kW  |
| operational current / rated value   | 125 A  |
| <b>Auxiliary circuit</b>  |        |
| number of CO contacts / for auxiliary contacts  | 0      |
| number of NC contacts / for auxiliary contacts  | 0      |
| number of NO contacts / for auxiliary contacts  | 0      |
| operating voltage / of auxiliary contacts / at AC / maximum   | 500 V  |
| continuous current / of the auxiliary contact / rated value   | 10 A   |
| insulation voltage / of the auxiliary switch / rated value  | 500 V  |
| <b>Suitability</b>  |        |
| suitability for use   |        |
| <ul style="list-style-type: none"> <li>• main switch</li> </ul>   | Yes    |
| <ul style="list-style-type: none"> <li>• switch disconnecter</li> </ul>   | Yes    |
| <ul style="list-style-type: none"> <li>• EMERGENCY OFF switch</li> </ul>  | No     |
| <ul style="list-style-type: none"> <li>• safety switch</li> </ul>   | Yes    |
| <ul style="list-style-type: none"> <li>• maintenance/repair switch</li> </ul>   | Yes    |
| <b>Appearance</b>   |        |
| color / of the actuating element  | black  |
| <b>Product details</b>  |        |
| product feature   |        |
| <ul style="list-style-type: none"> <li>• can be locked into OFF position</li> </ul>                                   | Yes    |
| number of bracket locks / maximum   | 3      |
| hasp thickness / of the bracket locks / minimum   | 5 mm   |
| hasp thickness / of the bracket locks / maximum   | 7.5 mm |
| product extension / optional  |        |
| <ul style="list-style-type: none"> <li>• motor drive</li> </ul>   | No     |
| <ul style="list-style-type: none"> <li>• voltage trigger</li> </ul>   | No     |
| <b>Short circuit</b>  |        |
| conditional short-circuit current / with line-side fuse protection  |        |
| <ul style="list-style-type: none"> <li>• at 440 V / by gG fuse / rated value</li> </ul>                               | 50 kA  |
| <ul style="list-style-type: none"> <li>• at 690 V / by gG fuse / rated value</li> </ul>                               | 50 kA  |
| <b>according UL</b>   |        |
| operational current / at AC / according to UL 489/UL 60947-4-1 / rated value  | 125 A  |
| operational current / at AC / according to UL 508/UL 60947-4-1 / rated value  | 125 A  |
| operating voltage / at AC / at 50/60 Hz / according to UL 489 / rated value   | 480 V  |
| operating voltage / at AC / at 50/60 Hz / according to UL 508/UL 60947-4-1 / rated value                              | 480 V  |
| active power [hp] / at AC / at 480 V / according to UL 508/UL 60947-4-1 / rated value                                 | 75     |

|   |  |
|---|--|
| short-time withstand current (SCCR) / at 480 V / according to UL 508/UL 60947-4-1 and UL 489        | 65 kA  |
| continuous current / of upstream fuse / according to UL / rated value                               | 125 A  |
| type of fuse / according to UL  | Class J  |
| <b>Number</b>   |  |
| number of connectable NC contacts / for auxiliary contacts / attachable / maximum                   | 3  |
| number of connectable NO contacts / for auxiliary contacts / attachable / maximum                   | 3  |
| number of connectable CO contacts / for auxiliary contacts / attachable / maximum                   | 0  |
| <b>Connections</b>  |  |
| AWG number / as coded connectable conductor cross section / solid                                   |  |
| • minimum   | 1  |
| • maximum   | 4/0  |
| AWG number / as coded connectable conductor cross section / solid / according to UL 489             |  |
| • minimum   | 1  |
| AWG number / as coded connectable conductor cross section / solid / according to CSA C22.2 No. 5-16 |  |
| • minimum   | 3  |
| type of connectable conductor cross-sections / for copper conductor                                 |  |
| • solid   | 1x (16 ...185mm <sup>2</sup> )   |
| • finely stranded / with core end processing  | 1x (16...150mm <sup>2</sup> )  |
| • stranded  | 1x (16...185mm <sup>2</sup> )  |
| type of connectable conductor cross-sections / for auxiliary contacts                               |  |
| • solid   | lateral auxiliary switch 2x (0,75 ... 2,5mm <sup>2</sup> ), 1x 4mm <sup>2</sup> ; front auxiliary switch 1x (0,75 ... 2,5mm <sup>2</sup> ) |
| • finely stranded / with core end processing  | lateral auxiliary switch 2x (0,75 ... 1,5mm <sup>2</sup> ), 1x 2,5mm <sup>2</sup> ; front auxiliary switch 1x 2,5mm <sup>2</sup>           |
| • stranded  | lateral auxiliary switch 2x (0,75 ... 2,5mm <sup>2</sup> ), 1x 4mm <sup>2</sup> ; front auxiliary switch 1x (0,75 ... 2,5mm <sup>2</sup> ) |
| type of electrical connection   |  |
| • for main current circuit  | box terminal   |
| • for auxiliary contacts  | connection terminals   |
| <b>Requirements</b>   |  |
| design of the fuse link   |  |
| • for short-circuit protection of the main circuit / required                                       | Fuse gG: 125 A   |
| • for short-circuit protection of the auxiliary switch / required                                   | fuse gL/gG: 10 A   |
| <b>Mechanical Design</b>  |  |
| height  | 178 mm   |
| width   | 113 mm   |
| depth   | 93 mm  |
| fastening method  | Built-in unit fixed-mounted version  |
| fastening method  |  |
| • 4-hole front mounting   | Yes  |
| • front mounting with central attachment  | No   |
| • rail mounting   | No   |
| net weight  | 1 650 g  |
| <b>Environmental conditions</b>   |  |
| ambient temperature / during operation  |  |
| • minimum   | -25 °C   |
| • maximum   | 55 °C  |
| ambient temperature / during storage / minimum  | -25 °C   |
| <b>General Product Approval</b>   | <b>Declaration of Conformity</b>   |



[Confirmation](#)



other

[Miscellaneous](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3LD5620-0TK11>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3LD5620-0TK11>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3LD5620-0TK11](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD5620-0TK11)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



