



(1)





NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ GOLD PLATED

-55°C ~ 125°C

5000MΩ min.

1000V AC rms

OPERATING TEMPERATURE:

.XX

±0.13

10.70

5.80

.XXX ±0.05

POWER/CO-AX CONTACT RATING: 10A (CURRENT) (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:



SW REFERENCE NO .: 630 COMBO ASSEMBLY DRAWN: C.B DATE: JAN. 01/2019 CHECKED: DATE:

> OF 2

> > ISSUE

1

1

SHEET



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



THESE DRAWINGS AND SPECIFICATIONS EDAC INC ARE THE PROPERTY OF EDAC INC..AND TORONTO, ONTARIO OR USED AS THE BASIS FOR THE CANADA MANUFACTURE OR SALE OF APPARATUS

COMBINATION D-SUB

SCALE: (IN C.A.D. 1:1) SHALL NOT BE REPRODUCED, OR COPIED 630-3W3-640-1TB DRAWING NUMBER: PART NUMBER: 630-3W3-640-1TB WITHOUT WRITTEN PERMISSION.

