SIEMENS

Data sheet

6ES7193-6BP20-0BB0



SIMATIC ET 200SP, BaseUnit BU20-P12+A4+0B, BU type B0, Push-in terminals, with 4 AUX terminals, bridged to the left, WxH: 20 mmx117 mm

Product type designation BU type 80 HW functional status FS10 and higher Supply voltage FS10 and higher Rated value (DC) See manual • For AUX bus 24 V. • For AUX bus 24 V. • For AUX bus 24 V. • For AUX bus 23 V • For AUX bus 230 V. • for AUX bus 230 V • for AUX bus 230 V • integrated No Current carrying capacity up to 60 °C, max. • for P1 and P2 bus, max. 10 A For process terminals, max. 5 A Hardware configuration 10 A Automatic encoding Yes Stots 1 • Number of stots 1 Potential separation 1 between backplane bus and supply voltage Yes between pocess terminals and supply voltage Yes between p	General information		
Supply voltage Rated value (DC) See manual • For P1 and P2 bus 24 V • For AUX bus 24 V; Equal potential group to P1/P2 bus or PE • for process terminals 24 V Rated value (AC) See manual • For P1 and P2 bus 230 V • For P1 and P2 bus 230 V • For P1 and P2 bus 230 V • Integrated No Mains filter • • integrated No Current carrying capacity up to 60 °C, max. • for P1 and P2 bus, max. 10 A For process terminals, max. 5 A Hardware configuration 10 A Automatic encoding Yes Slots 1 • Number of slots 1 Potential separation Yes between power bus and supply voltage Yes between process terminals and supply voltage No Isolation ested with	Product type designation	BU type B0	
Rated value (DC) See manual • For P1 and P2 bus 24 V • For AUX bus 24 V; Equal potential group to P1/P2 bus or PE • Ior process terminals 24 V Rated value (AC) See manual • For P1 and P2 bus 230 V • For AUX bus 230 V • For AUX bus 230 V • For P1 and P2 bus 230 V • For P1 and P2 bus 230 V • For AUX bus 230 V • Integrated No Current carrying capacity up to 60 °C, max. • Integrated No Current carrying capacity 10 A For P1 and P2 bus, max. 10 A For Process terminals, max. 5 A Hardware configuration Automatic encoding Ves Stots • Number of slots 1 Potential separation 1 between process terminals and supply voltage Yes between process terminals and supply voltage Yes Isolation 3100 V DC Ambient conditions -30 °C Ambient conditions -30 °C • vertical installation, min. -30 °C • vertical installation, max. 50 °C Altide during operation reliang to sea level -000 m;	HW functional status	FS10 and higher	
• For P1 and P2 bus 24 V • For AUX bus 24 V; Equal potential group to P1/P2 bus or PE • for process terminals 24 V Rated value (AC) See manual • For P1 and P2 bus 230 V • For AUX bus 230 V; Equal potential group to P1/P2 bus or PE • for process terminals 230 V • for process terminals 230 V • for process terminals 230 V • Mains filter • • integrated No Current carrying capacity up to 60 °C, max. 10 A For P1 and P2 bus, max. For P1 and P2 bus, max. 10 A For P1 and P2 bus, max. 10 A For P1 and P2 bus, max. 10 A For process terminals, max. 5 A Hardware configuration 10 A Automatic encoding Yes Slots 1 • Number of slots 1 Potential separation 20 V VC between process terminals and supply voltage Yes between process terminals and supply voltage Yes between process terminals and supply voltage No Isolation teted with 3 100 V DC Ambient conditions	Supply voltage		
• For AUX bus 24 V. Equal potential group to P1/P2 bus or PE • for process terminals 24 V Rated value (AC) See manual • For P1 and P2 bus 230 V • For AUX bus 230 V • For AUX bus 230 V • For AUX bus 230 V • Integrated No Current carrying capacity up to 60 °C, max. • Do 60 °C, max. 10 A For P1 and P2 bus, max. 5 A Hardware configuration Automatic encoding Yes Slots • Number of slots 1 Potential separation Detween backplane bus and supply voltage Detween power bus and supply voltage Yes between process terminals and supply voltage Yes between power bus and supply voltage Yes between portul installation, min. -	Rated value (DC)	See manual	
• for process terminals 24 V Rated value (AC) See manual • For P1 and P2 bus 230 V • For P1 and P2 bus 230 V; Equal potential group to P1/P2 bus or PE • for process terminals 230 V Mains filter 0 • integrated No Current carrying capacity 0 A Por P1 and P2 bus, max. 10 A For process terminals, max. 5 A Hardware configuration Automatic encoding Ves Slots • Number of slots 1 Potential separation Evene process terminals and supply voltage between process terminals and supply voltage Yes isolation tested with 3 100 V DC <	• For P1 and P2 bus	24 V	
Rated value (AC) See manual • For P1 and P2 bus 230 V • For AUX bus 230 V; Equal potential group to P1/P2 bus or PE • of process terminals 230 V Mains filter • integrated • integrated No Current carrying capacity up to 60 °C, max. For P1 and P2 bus, max. 10 A For P1 and P2 bus, max. 10 A For process terminals, max. 5 A Hardware configuration Automatic encoding Automatic encoding Yes Slots 1 • Number of slots 1 Potential separation Detween backplane bus and supply voltage between backplane bus and supply voltage Yes Isolation 100 V DC Ambient temperature during operation -30 °C • horizontal installation, min. -30 °C • vertical installation, max. 60 °C • vertical installation, max. 50 °C Altitude during operation relating to sea level -00 m; On request: installation altitudes greater than 2 000 m	• For AUX bus	24 V; Equal potential group to P1/P2 bus or PE	
• For P1 and P2 bus 230 V • For AUX bus 230 V; Equal potential group to P1/P2 bus or PE • for process terminals 230 V Mains filter 230 V • integrated No Current carrying capacity up to 60 °C, max. 10 A For P1 and P2 bus, max. For P1 and P2 bus, max. 10 A For P1 and P2 bus, max. 10 A For process terminals, max. 5 A Hardware configuration Automatic encoding Automatic encoding Yes Slots 1 • Number of slots 1 Potential separation Eetween process terminals and supply voltage between power bus and supply voltage Yes between power bus and supply voltage No Isolation 3 100 V DC Ambient temperature during operation - • horizontal installation, min. -30 °C • vertical installation, min.	 for process terminals 	24 V	
• For AUX bus 230 V; Equal potential group to P1/P2 bus or PE • for process terminals 230 V Mains filter 230 V • integrated No Current carrying capacity up to 60 °C, max. up to 60 °C, max. 10 A For P1 and P2 bus, max. 10 A For AUX bus, max. 10 A For chux bus, max. 5 A Hardware configuration 4utomatic encoding Automatic encoding Yes Slots 1 • Number of slots 1 Potential separation 5 between backplane bus and supply voltage Yes between power bus and supply voltage No Isolation 3 100 V DC Ambient temperature during operation - • horizontal installation, min. -30 °C • horizontal installation, min. -30 °C • vertical installation, min. -30 °C • vertical installation, min. -30 °C	Rated value (AC)	See manual	
• for process terminals 230 V Mains filter • integrated • integrated No Current carrying capacity up to 60 °C, max. For P1 and P2 bus, max. 10 A For P1 and P2 bus, max. 10 A For AUX bus, max. 10 A For process terminals, max. 5 A Hardware configuration Automatic encoding Automatic encoding Yes Slots 1 Potential separation between pocess terminals and supply voltage Yes between process terminals and supply voltage Yes between power bus and supply voltage Yes between power bus and supply voltage No Isolation tested with 3 100 V DC Ambient conditions Ambient temperature during operation - • horizontal installation, max. 60 °C • vertical installation, max. 50 °C • vertical installation, max. 50 °C • vertical installation metaluting to sea level - • installation atitfude above sea level, max.	• For P1 and P2 bus	230 V	
Mains filter • integrated No Current carrying capacity up to 60 °C, max. 10 A For P1 and P2 bus, max. 10 A For AUX bus, max. 10 A For P1 and P2 bus, max. 10 A For P1 and P2 bus, max. 10 A For P1 and P2 bus, max. 10 A For process terminals, max. 5 A Hardware configuration Automatic encoding Automatic encoding Yes Slots 1 • Number of slots 1 Potential separation Etween process terminals and supply voltage between power bus and supply voltage Yes between power bus and supply voltage Yes between power bus and supply voltage No Isolation 3 100 V DC Ambient conditions Ambient temperature during operation • horizontal installation, min. -30 °C • vertical installation, max. 60 °C • vertical installation, max. 50 °C • vertical installation, max. 50 °C • vertical installation, max. 50 °C • vertical installation relating to sea level e instal	• For AUX bus	230 V; Equal potential group to P1/P2 bus or PE	
• integrated No Current carrying capacity up to 60 °C, max. 10 A For P1 and P2 bus, max. For P1 and P2 bus, max. 10 A For process terminals, max. 10 A Hardware configuration 4 Automatic encoding Yes Slots 1 Potential separation 5 between backplane bus and supply voltage Yes between backplane bus and supply voltage Yes between process terminals and supply voltage Yes between power bus and supply voltage Yes between power bus and supply voltage Yes between power bus and supply voltage No Isolation 3 100 V DC Ambient conditions	 for process terminals 	230 V	
Current carrying capacity up to 60 °C, max. For P1 and P2 bus, max. For P1 and P2 bus, max. For AUX bus, max. For process terminals, max. For process terminals, max. Hardware configuration Automatic encoding Yes Slots • Number of slots 1 Potential separation between backplane bus and supply voltage Yes between process terminals and supply voltage Yes between process terminals and supply voltage Yes between process terminals and supply voltage Isolation Isolation Isolation tested with 3 100 V DC Ambient temperature during operation • horizontal installation, min. -30 °C • vertical installation, min. -30 °C • vertical installation, max. 50 °C Altitude during operation relating to sea level • Installation altitude above sea level, max. 2 000 m; On request: Installation altitudes greater than 2 000 m	Mains filter		
up to 60 °C, max. 10 A For P1 and P2 bus, max. 10 A For AUX bus, max. 10 A For process terminals, max. 5 A Hardware configuration Automatic encoding Automatic encoding Yes Slots 1 • Number of slots 1 Potential separation between backplane bus and supply voltage Yes between process terminals and supply voltage Yes between power bus and supply voltage Yes between power bus and supply voltage No Isolation Isolation tested with slotion tested with 3 100 V DC Ambient temperature during operation -30 °C • horizontal installation, min. -30 °C • vertical installation, min.	integrated	No	
For P1 and P2 bus, max. 10 A For AUX bus, max. 10 A For process terminals, max. 5 A Hardware configuration Automatic encoding Automatic encoding Yes Slots 1 Potential separation between process terminals and supply voltage between process terminals and supply voltage Yes between process terminals and supply voltage No Isolation Isolation Isolation 3 100 V DC Ambient temperature during operation • horizontal installation, min. • horizontal installation, min. -30 °C • vertical installation, min. -30 °C • vertical installation, max. 60 °C • vertical installation, max. 50 °C Altitude during operation relating to sea level • Installation altitude above sea level, max. • Installation altit	Current carrying capacity		
For AUX bus, max. 10 A For process terminals, max. 5 A Hardware configuration Automatic encoding Automatic encoding Yes Slots 1 Potential separation between backplane bus and supply voltage between process terminals and supply voltage Yes between process terminals and supply voltage Yes between process terminals and supply voltage Yes between process terminals and supply voltage No Isolation Isolation Isolation 3 100 V DC Ambient conditions -30 °C • horizontal installation, min. -30 °C • vertical installation, min. -30 °C • vertical installation, max. 50 °C Altitude during operation relating to sea level - • Installation altitude above sea level, max. 2 000 m; On request: Installation altitudes greater than 2 000 m	up to 60 °C, max.	10 A	
For process terminals, max. 5 A Hardware configuration Automatic encoding Automatic encoding Yes Slots 1 Potential separation 1 Detween backplane bus and supply voltage Yes between power bus and supply voltage Yes between power bus and supply voltage Yes between power bus and supply voltage Yes Isolation Isolation Isolation 3 100 V DC Ambient conditions Ambient temperature during operation horizontal installation, min. -30 °C vertical installation, max. 60 °C vertical installation, max. 50 °C Attitude during operation relating to sea level -000 m; On request: Installation altitudes greater than 2 000 m Accessories 2 000 m; On request: Installation altitudes greater than 2 000 m	For P1 and P2 bus, max.	10 A	
Hardware configuration Automatic encoding Yes Slots 1 Potential separation 1 between backplane bus and supply voltage Yes between process terminals and supply voltage Yes between power bus and supply voltage Yes between power bus and supply voltage Yes lsolation No Isolation tested with 3 100 V DC Ambient conditions -30 °C Arnbient temperature during operation -30 °C • horizontal installation, min. -30 °C • vertical installation, max. 60 °C • vertical installation, max. 50 °C Altitude during operation relating to sea level -000 m; On request: Installation altitudes greater than 2 000 m	For AUX bus, max.	10 A	
Automatic encoding Yes Slots 1 Potential separation 1 between backplane bus and supply voltage Yes between process terminals and supply voltage Yes between power bus and supply voltage Yes between power bus and supply voltage Yes between power bus and supply voltage No Isolation Isolation tested with Isolation tested with 3 100 V DC Ambient conditions -30 °C Ambient temperature during operation -30 °C • horizontal installation, min. -30 °C • vertical installation, max. 50 °C Altitude during operation relating to sea level - • Installation altitude above sea level, max. 2 000 m; On request: Installation altitudes greater than 2 000 m	For process terminals, max.	5 A	
Slots 1 Potential separation 1 between backplane bus and supply voltage Yes between process terminals and supply voltage Yes between power bus and supply voltage No Isolation Isolation Isolation tested with 3 100 V DC Ambient conditions -30 °C Ambient temperature during operation -30 °C • horizontal installation, min. -30 °C • vertical installation, min. -30 °C • vertical installation, min. -30 °C • lotizontal installation, min. -30 °C • lotizontal installation, min. -20 °C • lotizontal installation, min. -20 °C • lotizontal installation, min. -20 °C • lotizontal installation, max. 60 °C • vertical installation, max. 50 °C Altitude during operation relating to sea level - • Installation altitude above sea level, max. 2 000 m; On request: Installation altitudes greater than 2 000 m Accessories -	Hardware configuration		
• Number of slots 1 Potential separation	Automatic encoding	Yes	
Potential separation between backplane bus and supply voltage Yes between process terminals and supply voltage Yes between power bus and supply voltage No Isolation Isolation tested with 3 100 V DC Ambient conditions Ambient temperature during operation -30 °C • horizontal installation, min. -30 °C -30 °C • vertical installation, min. -30 °C -30 °C • vertical installation, max. 50 °C -30 °C • vertical installation attitude above sea level - - • Installation altitude above sea level 2 000 m; On request: Installation altitudes greater than 2 000 m	Slots		
between backplane bus and supply voltage Yes between process terminals and supply voltage Yes between power bus and supply voltage No Isolation Isolation Isolation tested with 3 100 V DC Ambient conditions	 Number of slots 	1	
between process terminals and supply voltage Yes between power bus and supply voltage No Isolation Isolation Isolation tested with 3 100 V DC Ambient conditions Ambient temperature during operation • horizontal installation, min. -30 °C • horizontal installation, max. 60 °C • vertical installation, min. -30 °C • vertical installation, max. 50 °C Altitude during operation relating to sea level 2 000 m; On request: Installation altitudes greater than 2 000 m Accessories Accessories	Potential separation		
between power bus and supply voltage No Isolation Isolation tested with 3 100 V DC Ambient conditions Ambient temperature during operation • • horizontal installation, min. -30 °C • • horizontal installation, max. 60 °C • • vertical installation, min. -30 °C • • vertical installation, max. 50 °C • Altitude during operation relating to sea level • • • Installation altitude above sea level, max. 2 000 m; On request: Installation altitudes greater than 2 000 m	between backplane bus and supply voltage	Yes	
Isolation Isolation tested with 3 100 V DC Ambient conditions Ambient temperature during operation • horizontal installation, min. -30 °C • horizontal installation, max. 60 °C • vertical installation, min. -30 °C • vertical installation, max. 50 °C Altitude during operation relating to sea level 50 °C • Installation altitude above sea level, max. 2 000 m; On request: Installation altitudes greater than 2 000 m	between process terminals and supply voltage	Yes	
Isolation tested with 3 100 V DC Ambient conditions Ambient temperature during operation • horizontal installation, min. • horizontal installation, max. • horizontal installation, max. • vertical installation, min. • vertical installation, max. • Unstallation altitude above sea level • Installation altitude above sea level, max. • Installation altitude above sea level, max. • Installation altitude above sea level, max. • O00 m; On request: Installation altitudes greater than 2 000 m Accessories	between power bus and supply voltage	No	
Ambient conditions Ambient temperature during operation • horizontal installation, min. -30 °C • horizontal installation, max. 60 °C • vertical installation, min. -30 °C • vertical installation, min. -30 °C • vertical installation, min. -30 °C • vertical installation, max. 50 °C Altitude during operation relating to sea level 50 °C • Installation altitude above sea level, max. 2 000 m; On request: Installation altitudes greater than 2 000 m Accessories Accessories	Isolation		
Ambient temperature during operation • horizontal installation, min. -30 °C • horizontal installation, max. 60 °C • vertical installation, min. -30 °C • vertical installation, min. -30 °C • vertical installation, max. 50 °C Altitude during operation relating to sea level 50 °C • Installation altitude above sea level, max. 2 000 m; On request: Installation altitudes greater than 2 000 m Accessories Accessories	Isolation tested with	3 100 V DC	
 horizontal installation, min. horizontal installation, max. horizontal installation, max. vertical installation, min. -30 °C vertical installation, max. 50 °C Altitude during operation relating to sea level Installation altitude above sea level, max. 2 000 m; On request: Installation altitudes greater than 2 000 m Accessories 	Ambient conditions		
• horizontal installation, max. 60 °C • vertical installation, min. -30 °C • vertical installation, max. 50 °C Altitude during operation relating to sea level 50 °C • Installation altitude above sea level, max. 2 000 m; On request: Installation altitudes greater than 2 000 m Accessories Accessories	Ambient temperature during operation		
vertical installation, min. vertical installation, max. vertical installation, max. Altitude during operation relating to sea level Installation altitude above sea level, max. Accessories Accessories	 horizontal installation, min. 	-30 °C	
vertical installation, max. 50 °C Altitude during operation relating to sea level Installation altitude above sea level, max. 2 000 m; On request: Installation altitudes greater than 2 000 m Accessories	 horizontal installation, max. 	60 °C	
Altitude during operation relating to sea level • Installation altitude above sea level, max. 2 000 m; On request: Installation altitudes greater than 2 000 m Accessories • Accessories	 vertical installation, min. 	-30 °C	
Installation altitude above sea level, max. 2 000 m; On request: Installation altitudes greater than 2 000 m Accessories	vertical installation, max.	50 °C	
Accessories	Altitude during operation relating to sea level		
	 Installation altitude above sea level, max. 	2 000 m; On request: Installation altitudes greater than 2 000 m	
Color coding labels	Accessories		
	Color coding labels		

• for AUX terminals	CC81 to CC83
connection method / header	
Terminals	
Terminal type	Push-in terminal
 Conductor cross-section, min. 	0.14 mm²; AWG 26
 Conductor cross-section, max. 	2.5 mm²; AWG 14
 Number of process terminals to I/O module 	12; Pro slot
 Number of terminals to AUX bus 	0
 Number of add-on terminals 	0
 Number of terminals with connection to P1 and P2 bus 	0; Pro slot
Dimensions	
Width	20 mm
Height	117 mm
Depth	35 mm
Weights	
Weight, approx.	48 g
last modified:	2/7/2021 🖸