


C0603X222K5RAC3317

SMD Auto X7R VW80808, Ceramic, 2200 pF, 10%, 50 VDC, X7R, SMD, MLCC, Automotive Grade, 0603 $\,$



Click here for the 3D model.

Chip Size 0603 L 1.6mm +/-0.17mm W 0.8mm +/-0.15mm T 0.8mm +/-0.15mm S 0.58mm MIN B 0.45mm +/-0.15mm	Dimensions	
W 0.8mm +/-0.15mm T 0.8mm +/-0.15mm S 0.58mm MIN	Chip Size	0603
T 0.8mm +/-0.15mm S 0.58mm MIN	L	1.6mm +/-0.17mm
S 0.58mm MIN	W	0.8mm +/-0.15mm
	Т	0.8mm +/-0.15mm
B 0.45mm +/-0.15mm	S	0.58mm MIN
	В	0.45mm +/-0.15mm

Packaging Specifications

Packaging Packaging Quantity

T&R, 330mm, Paper Tape 15000

General Information	
Series	SMD Auto X7R VW80808
Style	SMD Chip
Description	SMD, MLCC, Automotive Grade
Features	VW 80808 Specification Compliant
RoHS	Yes
Termination	Flexible Termination
Failure Rate	N/A
Qualifications	AEC-Q200
AEC-Q200	Yes
Shelf Life	152 Weeks

Specifications			
Capacitance	2200 pF		
Capacitance Tolerance	10%		
Voltage DC	50 VDC		
Dielectric Withstanding Voltage	125 VDC		
Temperature Range	-55/+125°C		
Temperature Coefficient	X7R		
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	15%, 1kHz 1.0Vrms		
Dissipation Factor	2.5%1kHz 1.0Vrms		
Insulation Resistance	100 GOhms		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.