

SEK CAB FLAT NSH RND AWG28/7 16P 30,48m



| Part number | 09 18 016 7008 |
|--------------------|--|
| Specification | SEK CAB FLAT NSH RND AWG28/7 16P 30,48m |
| HARTING eCatalogue | https://b2b.harting.com/09180167008 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | System cabling |
|------------------------------|--|
| Element | Bulk cables |
| Specification | Not assembled |
| Type of cable | Copper cable (round) |
| | |
| Version | |
| Cable length | 30.48 m |
| Number of cores | 16 |
| Core structure | AWG 28/7 |
| | |
| Technical characteristics | |
| Impedance | 100 Ω |
| Limiting temperature | -30 +75 °C unmoved -20 +75 °C moved |
| Conductor resistance @ 20 °C | ≤216 Ω/km |
| | |
| Material properties | |
| Material (cable) | PVC |
| Colour (cable) | Grey |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |

Page 1 / 2 | Creation date 2021-06-22 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Material properties

| REACH ANNEX XIV substances | No |
|-----------------------------------|-----------------------------------|
| REACH SVHC substances | No |
| | |
| Specifications and approvals | |
| Specifications | UL 1581 Sec. 1061 UL PLCC, CL2 |
| CE | Yes |
| | |
| | |
| Commercial data | |
| Commercial data Packaging size | 1 |
| | 1 2,023.1 g |
| Packaging size | |
| Packaging size Net weight | 2,023.1 g |