

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER. .X ±0.25




| | ISSUE NUMBER |
|--------|--------------|
| | ORIGINAL |
| \neg | |

(1)








NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED



| POWER/CO-AX CONTACT RATING: | 10A (CURRENT) |
|--------------------------------|----------------|
| (IF PRESENT) | |
| SIGNAL CONTACT CURRENT RATING: | 5A PER CONTACT |
| SIGNAL CONTACT RESISTANCE: | 10mΩ MAX. |
| | |
| | E000MO min |

.XX ±0.13 .XXX ±0.05


INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

OPERATING TEMPERATURE:


5000MΩ min.

1000V AC rms

-55°C ~ 125°C



| | | | SW REFERENCE NO.: 629 COMBO ASSEMBLY | | |
|-----------------|---|--|--------------------------------------|------------------|-------|
| | COMBINATION D-SUB | | | DATE: JAN. 01/20 | 19 |
| | | | CHECKED: | DATE: | |
| EDAC | EDAC INC TORONTO, ONTARIO CANADA INECTION TO QUALITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1) | SHEET 1 OF | 2 |
| | | | DRAWING NUMBER: 629-21W | 1240-1N3 | ISSUE |
| YOUR CONNECTION | | | PART NUMBER: 629-21W | 1240-1N3 | 1 |





12.50 8.30

100

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

