	<u>م ا</u>	г	m		0			
LAYOUT SHOWN AS EXAMPLE Address Listed on NUL-DT-38999 Series III Shell Materia Solution Repeature Range Solution Repea								
CHARACTERISTICS Standard : Based on MIL-DTL 38999 Series II Schell Plating : Compector dimension Insulator : Compector dimension : Contact Plating :						LAYOUT SHOWN AS EXAMPLE		
-Standard : Based on MIL-DTL-38999 Series III Shell Material : Composite -Shell Material : Composite -Shell Material : Composite -Insulator : Dimetucionmentation -Contacts : Copper Alloy -Seed R Products and Accessories : Dimetucionmentation -Ourability : Solutation issued by ethic of the Partics or by a trich party (professional recommendation, technical notice.) -Ourability : Solutation issued by ethic of the Partics or by a trich party (professional recommendation, technical notice.) -Ourability : Solutation issued by ethic of the Partics or by a trich party (professional recommendation, technical notice.) -Durability : Solutation issued by ethic of the Partics or by a trich party (professional recommendation, technical notice.) -Durability : Solutation issued by ethic of the Partics or by a trich party (professional recommendation, technical notice.) -Durability : Solutation issued by ethic of the Partics or by a trich party (professional recommendation, technical notice.) -Temperature Range : -65°C to +175°C -Sait Spray : 2000 hours -Mass : 45.7 g ± 10% Shiell TYPE : Play in the second comment is the property of the partics or cost or prophy of the partis or costore partice or costore partice or cost or pro		Keying Shown a	s example					
Shell Material : Composite -Shell Material : Composite -Shell Material : Composite -Shell Material : Composite -Contact S : Copper Alloy -Seals & Grommet : Slicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : S00 Mating cycles -Delivered with Souriau contacts and Accessories PN: 8D519J11SE -Temperature Range : 65°C to +175°C -Salt Spray : 2000 hours -Mass : 45.7 g ± 10% BASIC SERIES: 8D 5 8D 5 19 J SHELL TYPE : Plag with RFI Shielding J 11 CONTACT TYPE : Standard Crimp Contact 85 SHELL SIZE : 19 ORIENTATION : E SOURIAU WWW.SOURIAU.COM The document is there or to stolk and interacted without persistion or to stolk and interacted without persistion or to stolk and interacted without persiston or to stolk and interacted without persisti		F						
- Durability : 500 Mating cycles - Delivered with Souriau contacts and Accessories - Temperature Range : -65°C to +175°C - Salt Spray : 2000 hours - Mass : 45.7 g ± 10% BASIC SERIES: 8D SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Souriau SHELL SIZE : 19 0RIENTATION :: E PLATING : J PLATING : J	-Shell Material: Composite-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer		ØS 38.5 Max Z' 31.5 Max		due to a u the Specificatio	use of the Products which does not ons issued by either of the Parties o essional recommendation, technical Country Jur	comply with or by a third party I notice.) isdiction & Control List	
-Temperature Range : -65°C to +175°C -Salt Spray : 2000 hours -Mass : 45.7 g ± 10% BASIC SERIES: 8D 5 - 19 J 11 5 C SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 19 PLATING : J = Olive drab Cadmium PLATING : J = Olive drab Cadmium CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) SHELL SIZE : 19 PLATING : J = Olive drab Cadmium CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET	-Durability : 500 Mating cycles			Γ			NOT LISTED	
-Salt Spray : 2000 hours -Mass : 45.7 g ± 10% BASIC SERIES: 8D 5 19 J 11 S E CONTACT TYPE : Plug with RFI Shielding SHELL SIZE : 19 PLATING : J = Olive drab Cadmium ORIENTATION : E SHELL SIZE : 19 PLATING : J = Olive drab Cadmium SHET					I			
BASIC SERIES: BD 5 19 J 11 S E Customer Drawing SHELL TYPE Bug with RFI Shielding J 11 S E Contact Type Scale General linear Tolerances: NPRDS / PROJECT SHELL TYPE Standard Crimp Contact ORIENTATION : E SCALE General linear Tolerances: NPRDS / PROJECT SHELL SIZE : 19 CONTACT TYPE SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU PLATING : J Olive drab Cadmium CONTACT LAYOUT : 19-11 FORMAT SOURIAU DRG N° SHEET				A	18-10-2016 First Release			
BASIC SERIES: 8D 5 19 J 11 S E SHELL TYPE Plug with RFI Shielding Image: Standard Crimp Contact Image: Standard Crimp Con	-Mass : 45.7 g ± 10%						CUSTOMER DRAWING	MOD N°
BASIC SERIES. ab 3 - 19 11 3 e A Tolerances: B59 SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact ORIENTATION : E NA MA Image: Contact is the property of SOURIAU.COM Step of Souriau SHELL SIZE : 19 CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) This document is the property of SOURIAU.COM SOURIAU This document is the property of SOURIAU.COM SOURIAU it must not be reproduced or communicated without permission PLATING : J = Olive drab Cadmium CONTACT LAYOUT : 19-11 FORMAT SOURIAU DRG N° SHEET				1	TITLE	Composite Plug	8D series	
CONTACT TYPE : Standard Crimp Contact ORIENTATION : E SHELL SIZE : 19 CONTACT TYPE : SOCKET(500 Matings) PLATING : J = Olive drab Cadmium CONTACT LAYOUT : 19-11 FORMAT SOURIAU FORMAT SOURIAU CONTACT LAYOUT : 19-11		11 S E				Tolerances:		
SHELL SIZE : 19 CONTACT TYPE : SOCKET(500 Matings) communicated without permission PLATING : J = Olive drab Cadmium CONTACT LAYOUT : 19-11 FORMAT SOURIAU DRG N° SHEET	CONTACT TYPE : Standard Crimp Contact			SU		w.souriau.com	SOURIAU	
					AT		communicated without per	mission
	PLATING : J = Olive drab Cadmium		CONTACT LAYOUT	. 15-11		SOURIAU DRG N 8D519J11SE-C	-	SHEET

