

CERTIFICATE OF COMPLIANCE

Certificate Number 20181120- E139109
Report Reference E139109-A6055-UL
Issue Date 2018-NOVEMBER-20

Issued to: XP POWER L L C
15641 RED HILL AVE, SUITE 100
TUSTIN CA 92780, UNITED STATES

**This certificate confirms that
representative samples of**

POWER SUPPLIES FOR USE IN AUDIO/VIDEO,
INFORMATION AND COMMUNICATION TECHNOLOGY
EQUIPMENT
Switching Power Supply
Models: HPU1K5PSXX, Where XX can be any number
between 12-48. May also be provided with additional suffix
"SF" or "-M".

Have been investigated by UL in accordance with the
component requirements in the Standard(s) indicated on
this Certificate. UL Recognized components are incomplete
in certain constructional features or restricted in
performance capabilities and are intended for installation in
complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety:

UL 62368-1, (Audio/video, information and communication
technology equipment Part 1: Safety requirements).
CAN/CSA C22.2 No. 62368-1-14, (Audio/video, information and
communication technology equipment Part 1: Safety
requirements).


Additional Information:

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified
and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



UL TEST REPORT AND PROCEDURE

Standard:	UL 62368-1, 2nd Ed, 2014-12-01 (Audio/video, information and communication technology equipment Part 1: Safety requirements) CAN/CSA C22.2 No. 62368-1-14, 2nd Ed (Audio/video, information and communication technology equipment Part 1: Safety requirements)
Certification Type:	Component Recognition
CCN:	QQJQ2, QQJQ8 (Power Supplies for Use in Audio/Video, Information and Communication Technology Equipment)
Complementary CCN:	N/A
Product:	Switching Power Supply
Model:	HPU1K5PSXX Where XX can be any number between 12-48. May also be provided with additional suffix "SF" or "-M".
Rating:	INPUT ~ 100 - 240VAC 50/60Hz 16.5A OUTPUT : See Model Differences.
Applicant Name and Address:	XP POWER L L C 15641 RED HILL AVE, SUITE 100 TUSTIN CA 92780 UNITED STATES

This is to certify that representative samples of the products covered by this Test Report have been investigated in accordance with the above referenced Standards. The products have been found to comply with the requirements covering the category and the products are judged to be eligible for Follow-Up Service under the indicated Test Procedure. The manufacturer is authorized to use the UL Mark on such products which comply with this Test Report and any other applicable requirements of UL LLC ('UL') in accordance with the Follow-Up Service Agreement. Only those products which properly bear the UL Mark are considered as being covered by UL's Follow-Up Service under the indicated Test Procedure.

The applicant is authorized to reproduce the referenced Test Report provided it is reproduced in its entirety.

UL authorizes the applicant to reproduce the latest pages of the referenced Test Report consisting of the first page of the Specific Technical Criteria through to the end of the Conditions of Acceptability.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL.

Prepared By: Adam Tangocci / Project Handler Reviewed By: Gregory Ray / Reviewer

Supporting Documentation

The following documents located at the beginning of this Procedure supplement the requirements of this Test Report:

A. Authorization - The Authorization page may include additional Factory Identification Code markings.

B. Generic Inspection Instructions -

- i. Part AC details important information which may be applicable to products covered by this Procedure. Products described in this Test Report must comply with any applicable items listed unless otherwise stated in the body of this Test Report.
- ii. Part AE details any requirements which may be applicable to all products covered by this Procedure. Products described in this Test Report must comply with any applicable items listed unless otherwise stated in the body of each Test Report.
- iii. Part AF details the requirements for the UL Certification Mark which is not controlled by the technical standard used to investigate these products. Products are permitted to bear only the Certification Mark(s) corresponding to the countries for which it is certified, as indicated in each Test Report.

Product Description

The product is a component AC-DC power supply for building-in, provided with an overall metal enclosure, incorporating primary and SELV components.

The main PWB is secured to the chassis bottom by multiple machine screws. An insulating sheet is installed between PWB and chassis, wrapped around the board assembly, covering the sides and extending over the top. The control PWB is mounted vertically on the side of the main PWB and secured by multi-pin soldering.

The unit is provided with 2 cooling fans mounted internally behind the rear panel acting as fan guard.

Model Differences

The power supplies in the series are differentiated by the output voltage and current ratings, number of turns of primary/secondary windings in the Transformers (T2 (Power)) and minor differences in the secondary circuit components and PWB layout.

See below for Model Ratings Table Below:

- Model HPU1K5PS12: Output Rated: 10.1 Vdc to 13.5 Vdc, 100 A Max (1200 W)
- Model HPU1K5PS15: Output Rated: 13.6 Vdc to 17 Vdc, 80 A Max (1200 W)
- Model HPU1K5PS18: Output Rated: 17.1 Vdc to 21 Vdc, 66.7 A (1200 W)
- Model HPU1K5PS24: Output Rated: 21.1 Vdc to 26 Vdc, 50 A (1200 W)
- Model HPU1K5PS24: Output Rated: 21.1 Vdc to 26 Vdc, 62.5 A Max (1500 W for Input rated: 180-240 Vac)
- Model HPU1K5PS28: Output Rated: 26.1 Vdc to 31 Vdc, 43 A (1200 W)
- Model HPU1K5PS28: Output Rated: 26.1 Vdc to 31 Vdc, 53 A Max (1500 W for Input rated: 180-240 Vac)
- Model HPU1K5PS33: Output Rated: 31.1 Vdc to 33 Vdc, 36.4 A (1200 W)
- Model HPU1K5PS33: Output Rated: 31.1 Vdc to 33 Vdc, 45.5 A Max (1500 W for Input rated: 180-240 Vac)
- Model HPU1K5PS36: Output Rated: 33.1 Vdc to 42 Vdc, 33.3 A (1200 W)
- Model HPU1K5PS36: Output Rated: 33.1 Vdc to 42 Vdc, 41.7 A Max (1500 W for Input rated: 180-240 Vac)
- Model HPU1K5PS48: Output Rated: 42.1 Vdc to 54 Vdc, 25 A (1200 W)
- Model HPU1K5PS48: Output Rated: 42.1 Vdc to 54 Vdc, 31.25 A (1500 W for Input rated: 180-240 Vac)

Suffix "SF" indicates single fuse provided in the line side of the primary.

Suffix "-M" is identical to HPU1K5PSXX except for model designation for marketing purposes.

See Enclosure-Miscellaneous for details.

Test Item Particulars

Classification of use by	Ordinary person
Supply Connection	AC Mains
Supply % Tolerance	+10%/-10%
Supply Connection – Type	For building-in
Considered current rating of protective device as part of building or equipment installation	20 A; building;
Equipment mobility	for building-in
Over voltage category (OVC)	OVC II OVC II
Class of equipment	Not Classified
Access location	N/A
Pollution degree (PD)	PD 2
Manufacturer’s specified maximum operating ambient	50°C at full-rated output load, 60°C at 75% of output load, 70°C at 50% of output load. °C
IP protection class	IPX0
Power Systems	TN
Altitude during operation (m)	3048 m
Altitude of test laboratory (m)	2000 m or less
Mass of equipment (kg)	3

Technical Considerations

- The product was submitted and evaluated for use at the maximum ambient temperature (T_{ma}) permitted by the manufacturer's specification of : 50°C at full-rated output load, 60°C at 75% of output load, 70°C at 50% of output load.
- The product is intended for use on the following power systems : TN
-
- The equipment disconnect device is considered to be : To be determined in the end-product.
- Required Clearances have been adjusted by multiplying the clearance at sea level by a factor of 1.15 for operating at an altitude of 3048 meters. The correction factor is based on barometric pressure of 70kPa. If the calculated Clearance exceeded the Creepage, the Creepage was adjusted to the value of clearance.

Engineering Conditions of Acceptability

For use only in or with complete equipment where the acceptability of the combination is determined by UL LLC. When installed in an end-product, consideration must be given to the following:

- The following product-line tests are conducted for this product : Electric Strength
-
- The following output circuits are at ES1 energy levels : All Outputs
- The following output circuits are at PS3 energy levels : All Outputs
- The maximum investigated branch circuit rating is : 20 A
-
- The investigated Pollution Degree is : 2
-
- Proper bonding to the end-product main protective earthing termination is : Required (Class I)
- An investigation of the protective bonding terminals has : Not been conducted
-
- The following input terminals/connectors must be connected to the end-product supply neutral : AC N
- The following end-product enclosures are required : Mechanical, Fire, Electrical
- The following magnetic devices (e.g. transformers or inductor) are provided with an OBJY2 insulation system with the indicated rating greater than Class A (105°C) : L1, L2, L4, L5, L6, L7, L8, T1(Bias), T2(Power), T1 (Drive), T3 (Drive), T4 (Current). T5 (Current) are Class F (155°C)
- The power supply was evaluated to be used at altitudes up to : "3048 m"
-
- When installed in a Class I end product, the power supply shall be mounted in a manner that provides the minimum required Clearance between the primary side of power supply and protectively earthed accessible conductive parts.
- Heatsinks are floating and considered live. They should not be accessible in the end-product.
- A suitable main disconnect device shall be provided in the end product.
- For models without suffix "SF": The power supplies covered by this report have a fuse in the neutral of the primary circuit. The need for a marking to warn a service person of the hazards associated with double pole/neutral fusing shall be considered in the end product.
- Consideration to repeating the Touch Current test should be given in the end-product evaluation.
- The power supplies in this report have been subject to Capacitance Discharge testing. Additionally, all associated component safeguards have been assessed to the applicable requirement in Annex G.10. Additional testing should not be needed if directly connected to mains e.g. using an appliance inlet, wiring terminals, etc.