



Material and Finish

- Shell: Steel, nickel plated
- Insulator: PBT thermoplastic with glass-fiber reinforcement, UL94V-0 rated
- Color: Black
- Contact Material:
 - Socket - Phosphor Bronze
 - Plug - Brass
- Contact Plating Options:
 - Standard: gold flash on mating end, tin on termination end, nickel underplate on entire contact
 - 15 Option: 15u" gold on mating end, tin on termination end, nickel underplate on entire contact
 - 30 Option: 30u" gold on mating end, tin on termination end, nickel underplate on entire contact

Electrical Specifications

- Rated Current: 1.2A
- Rated Voltage: 30V RMS
- Insulation Resistance: more than 1000 megohms at 500V DC
- Contact Resistance: 13 milliohms max.
- Dielectric Withstanding Voltage: 1000V for 1 minute
- Operating Temperature: -55°C to +105°C



Part Number	Contact Area Plating Finish
K42X-E9S/P-A4NJ	Gold Flash (standard)
K42X-E9S/P-A4NJ15	15u" Gold (15 option)
K42X-E9S/P-A4NJ30	30u" Gold (30 option)

Recommended PCB Layout (Bottom View)




Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	11/09/09	New Drawing	S. Vien	H. MA	S. Vien	09/03/09
A2	12/31/17	ECO #17-037	J. Elbanna	C. Furumasu		
A3	04/02/19	ECO #19-020	H. MA	D. Shehan		

K42X-E9S/P-A4NJ

D-Sub, 9 Female/9 Male, RoHS Compliant

4 Grounding BoardLocks, 0.750" Spacing, JS



UNITS
mm