

MT-1707

3 5/6 TRUE-RMS MULTIMETER


MT-1707 3-5/6 True-RMS Multimeter is designed for accurate measurements, ideal for a wide variety of electrical and electronic testing applications.

CE CAT III 1000V
CAT IV 600V



30 Positions, Full Functions

- Special design for ACV/ACA True-RMS measurement.
- Measuring DCV/ACV/DCA/ACA/resistance, capacitance/Hz duty cycle/temperature/live wire test and diode.



Non Contact Voltage Detector

tests AC 90-1000V

Voltage level indicator

To show the voltage signal intensity

Friendly Extra Functions

Continuity with beeper, duty cycle, data hold, auto power off, LED light, low battery indication and input alert protection ensures uninterrupted operation and long life.



Specifications	MT-1707
DCV	600mV/6V/60V/600V/1000V ±(0.5%+3d)
ACV TrueRMS	6V/60V ±(0.8%+3d) 600V/750V ±(1%+10d) Frequency Response : 40Hz-1KHz
DCA	60uA/6mA/60mA/600mA±(0.8%+3d) 10.00A±(1.2%+3d)
ACA TrueRMS	60mA/600mA±(1%+3d) 10.00A±(1.5%+3d) Frequency Response : 40Hz-1KHz
Frequency (Hz)	9.999Hz/99.99Hz/999.9Hz/9.999KHz/ 99.99KHz/999.9KHz/9.99MHz ±(1.0%+3d)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ±(0.8%+3d) 60MΩ±(1.2%+30d)
Capacitance	6nF±(4.0%+30d) 60nF/600nF/6uF/60uF/600uF/6mF±(4.0%+3d) 100mF ±(5.0%+3d)
Temperature	-20°C~1000°C/-4°F~1832°F±(1.0%+3d)
Fuse	FF600mA/1000V, FF10A/1000V
Power	4 x 1.5V AA Batteries (not included)
Weight	340g (without battery)
Dimension	192 (L)×89 (W)×55(H)mm / 7.5"×3.5"×2.5"
Individual packing	Color Box



ACV True-RMS



Live wire test



LED light



Non contact voltage detector