



## Main

Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter 50986.12 Gal/hr(US) (193 m <sup>3</sup> /h)
[Us] rated supply voltage	25...55.2 V
Input voltage	48 V DC

## Complementary

Absorbed power	8.7 W
Line Rated Current	0.18 A
Noise level < at	50...51 dB
Bearing type	Ball
Height	External 10.55 in (268 mm)
Width	External 9.76 in (248 mm)
Depth	External 4.09 in (104 mm)
Cut-out dimensions	223 x 223 mm
Net Weight	1.79 lb(US) (0.81 kg)
Material	Outlet grille injected thermoplastic (ASA PC)
Color	Outlet grille Gray RAL 7035)
Ambient Air Temperature for Operation	14...158 °F (-10...70 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Maximum pressure	50 Pa flow rate 0 m <sup>3</sup> /h
Connections - Terminals	Cable
IP degree of protection	IP54
Device composition	1 axial motor 2 protective grille on the front and rear surfaces 1 filter front of axial motor 1 outlet grille front 1 cut-out template 1 power cord
Condition of use	Surrounding environment must be relatively clean Outside temperature must be 5 °C lower than inside temperature Overfrequent filter replacement should be avoided Filter must be cleaned and replaced regularly Flow rates depends on the work point, see ProClima software

## Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480151279
Nbr. of units in pkg.	1
Package weight(Lbs)	2.32 lb(US) (1.054 kg)
Returnability	No
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.09 in (18.0 cm)
Package 1 width	7.28 in (18.5 cm)
Package 1 Length	10.04 in (25.5 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	4
Package 2 Weight	9.29 lb(US) (4.216 kg)
Package 2 Height	15.75 in (40.0 cm)
Package 2 width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	18 months
----------	-----------