

# Power Extension Cord, Right-Angle NEMA 5-15P to NEMA 5-15R - 13A, 120V, 16 AWG, 1 ft. (0.31 m), Black

MODEL NUMBER: P024-001-13A15D









1 ft. extension cord with 5-15R and right-angle 5-15P connectors connects bulky power transformers without blocking adjacent outlets.

#### **Features**

1-ft. (0.31 m) Extension Cord Connects PCs, Printers, Monitors and Other EquipmentThis cord is recommended for home/office desktop computer applications, home theater setups or other applications where multiple devices are plugged into a surge protector, PDU or UPS system. It allows you to connect bulky power adapters to a NEMA 5-15R outlet without blocking adjacent outlets. It's also an excellent replacement for a lost or damaged extension cord. The 1-ft. (0.31 m) length helps reduce cable clutter.

Right-Angle Plug Makes Connecting in Tight Spaces EasierThe space-saving right-angle NEMA 5-15P connector is easy to install in confined spaces, such as behind your computer desk or workstation. The right-angle construction also relieves strain on the cable and connector and prevents the cable from bending awkwardly.

#### **Highlights**

- Recommended for powering computers, printers and other home/office peripherals
- Right-angle plug allows easier connection in confined or hardto-reach spaces
- 1-ft. (0.31 m) length allows flexibility in placing devices, while avoiding cable clutter
- Ideal replacement for damaged or missing 1-ft. (0.31 m) extension cord

### **Applications**

- Connect devices like computers, servers and monitors to a PDU in your data center
- Extend an existing power connection up to 1-ft. (0.31 m) to more easily place a device or reach a power source in a rack
- Provide a high-quality replacement for a worn-out or missing power cord

#### Package Includes

 P024-001-13A15D 1-ft. (0.31 m) Extension Cord, Right-Angle NEMA 5-15P to NEMA 5-15R, Black

## **Specifications**

| OVERVIEW                    |   |  |
|-----------------------------|---|--|
| UPC Code                    | 037332243812                                      |  |
| Device Compatibility        | Computer; Monitor/HDTV; Printer; Server; UPS; PDU |  |
| Country/Region              | North America                                     |  |
|                             |   |  |
| INPUT                       |   |  |
| Maximum Input Amps          | 13  |  |
| Voltage Compatibility (VAC) | 125   |  |





| PHYSICAL                            |                             |  |
|-------------------------------------|-----------------------------|--|
| Plug Color                          | Black                       |  |
| Cable Jacket Color                  | Black                       |  |
| Cable Jacket Material               | PVC                         |  |
| Cable Jacket Rating                 | FT2                         |  |
| Power Cord Jacket Type              | SJT                         |  |
| Cable Outer Diameter (OD)           | 9mm                         |  |
| Number of Conductors                | 3                           |  |
| Wire Gauge (AWG)                    | 16                          |  |
| Wire Gauge (OD - mm²)               | 1.31                        |  |
| Cable Length (ft.)                  | 1                           |  |
| Cable Length (m)                    | 0.30                        |  |
| ENVIRONMENTAL                       |                             |  |
| Operating Temperature Range         | -4 TO 140 F (- 20° TO 60°C) |  |
| Storage Temperature Range           | -4 TO 140 F (- 20° TO 60°C) |  |
| Operating Humidity Range            | 20-80% RH                   |  |
| Storage Humidity Range              | 20-80% RH                   |  |
| CONNECTIONS                         |                             |  |
| Side A - Connector 1                | NEMA 5-15P                  |  |
| Side B - Connector 1                | NEMA 5-15R                  |  |
| FEATURES & SPECIFICATIONS           |                             |  |
| High Voltage                        | No                          |  |
| Locking Plug                        | No                          |  |
| Angled Plug                         | Yes                         |  |
| STANDARDS & COMPLIANCE              |                             |  |
| Certifications                      | UL/Cul                      |  |
| Approvals                           | UL/CSA                      |  |
| WARRANTY                            |                             |  |
| Product Warranty Period (Worldwide) | Lifetime limited warranty   |  |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>