



PCB LAYOUT: COMPONENT SIDE
RECOMMENDED PCB THICKNESS : .100/(2.54) MAX.

CIRCUIT SIZE	"A"	"B"	C
04	$\frac{.512}{13.00}$	$\frac{.118}{3.00}$	$\frac{.472}{12.00}$
06	$\frac{.630}{16.00}$	$\frac{.236}{6.00}$	$\frac{.590}{15.00}$
08	$\frac{.748}{19.00}$	$\frac{.354}{9.00}$	$\frac{.709}{18.00}$
10	$\frac{.866}{22.00}$	$\frac{.472}{12.00}$	$\frac{.827}{21.00}$
12	$\frac{.984}{25.00}$	$\frac{.590}{15.00}$	$\frac{.945}{24.00}$
14	$\frac{1.102}{28.00}$	$\frac{.709}{18.00}$	$\frac{1.063}{27.00}$
16	$\frac{1.220}{31.00}$	$\frac{.827}{21.00}$	$\frac{1.181}{30.00}$
18	$\frac{1.338}{34.00}$	$\frac{.945}{24.00}$	$\frac{1.299}{33.00}$
20	$\frac{1.457}{37.00}$	$\frac{1.063}{27.00}$	$\frac{1.417}{36.00}$
22	$\frac{1.575}{40.00}$	$\frac{1.181}{30.00}$	$\frac{1.535}{39.00}$
24	$\frac{1.693}{43.00}$	$\frac{1.299}{33.00}$	$\frac{1.653}{42.00}$

MATERIAL NUMBER	NUMBER OF POSITIONS	PLATING OPTION
44432-0410	04	D
44432-0411	04	B
44432-0412	04	C
44432-0610	06	D
44432-0611	06	B
44432-0612	06	C
44432-0810	08	D
44432-0811	08	B
44432-0812	08	C
44432-1010	10	D
44432-1011	10	B
44432-1012	10	C
44432-1210	12	D
44432-1211	12	B
44432-1212	12	C
44432-1410	14	D
44432-1411	14	B
44432-1412	14	C
44432-1610	16	D
44432-1611	16	B
44432-1612	16	C
44432-1810	18	D
44432-1811	18	B
44432-1812	18	C
44432-2010	20	D
44432-2011	20	B
44432-2012	20	C
44432-2210	22	D
44432-2211	22	B
44432-2212	22	C
44432-2410	24	D
44432-2411	24	B
44432-2412	24	C

NOTES:

- MATERIALS-**
HOUSING: LCP, GLASS FILLED, UL94V-0, COLOR-BLACK (LOW HALOGEN)
TERMINAL: BRASS ALLOY
- FINISH:**
B = .00015/(0.00038) MIN. SELECT GOLD IN CONTACT AREA, .000100/(0.00254) MIN. SELECT MATTE TIN ON SOLDER TAILS, BOTH OVER .000050/(0.00127) MIN. NICKEL.
C = .000030/(0.00076) MIN. SELECT GOLD IN CONTACT AREA, .000100/(0.00254) MIN. SELECT MATTE TIN ON SOLDER TAILS, BOTH OVER .000050/(0.00127) MIN. NICKEL.
D = .000100/(0.00254) MIN. MATTE TIN OVER .000050/(0.00127) MIN. NICKEL.
- PRODUCT SPECIFICATION:** PS-44300-001
- PACKAGING SPECIFICATION:** PK-44432-001
- THIS ASSEMBLY MATES WITH MOLEX BMI PANEL MOUNT RECEPTACLE 44133 SERIES, VERTICAL PCB 44769 SERIES, AND RIGHT ANGLE PCB 44764 SERIES.**
- THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.**

<p>THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION</p>																				
<p>SYMBOLS</p> <p>▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0</p>	<p>DIMENSION UNITS</p> <p>IN/MM</p>	<p>SCALE</p> <p>NTS</p>	<p>CURRENT REV DESC: CHANGE 4, 6, 8, & 20 CKT TO MATTE TIN</p>																	
	<p>GENERAL TOLERANCES (UNLESS SPECIFIED)</p> <table border="1"> <thead> <tr> <th></th> <th>MM</th> <th>INCH</th> </tr> </thead> <tbody> <tr> <td>4 PLACES ±</td> <td></td> <td></td> </tr> <tr> <td>3 PLACES ±</td> <td></td> <td>± 0.01</td> </tr> <tr> <td>2 PLACES ±</td> <td>0.25</td> <td>± 0.015</td> </tr> <tr> <td>1 PLACE ±</td> <td>0.38</td> <td></td> </tr> <tr> <td>0 PLACES ±</td> <td></td> <td></td> </tr> </tbody> </table>			MM	INCH	4 PLACES ±			3 PLACES ±		± 0.01	2 PLACES ±	0.25	± 0.015	1 PLACE ±	0.38		0 PLACES ±		
	MM	INCH																		
4 PLACES ±																				
3 PLACES ±		± 0.01																		
2 PLACES ±	0.25	± 0.015																		
1 PLACE ±	0.38																			
0 PLACES ±																				
<p>INITIAL REVISION:</p> <p>DRWN: MMSTROH 2012/04/20 APPR: FSMITH 2012/08/27</p>		<p>THIRD ANGLE PROJECTION</p> <p>DRAWING SERIES</p> <p>C-SIZE 44432</p>	<p>PRODUCT CUSTOMER DRAWING</p> <p>DOCUMENT NUMBER: SD-44432-005</p> <p>DOC TYPE: PSD DOC PART: 001 REVISION: B</p>																	
<p>DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</p>		<p>SEE TABLE</p>	<p>CUSTOMER: GENERAL MARKET</p> <p>SHEET NUMBER: 1 OF 1</p>																	