


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00580	Connector, USB A micro plug, molding style, 180°, nickel plated shell, black insulator	2	
2	30-01272	Wire, 4C, 1PR + 2C, 28 AWG, UL2725, 30V, 80C, 4.1 mm, shielded, VW-1, PVC, 79A, USB 2.0, nylon braid	1	
3	24-00317	Overmold, plug, USB micro and mini, slim design for aluminum shell	2	PVC, black
4	55-00117	USB mini & micro aluminum shell, 13x10.5x6.8 mm	2	black



Wiring diagram		
50-00580	Wire Color	50-00580
1	Red	1
2	White	2
3	Green	3
4 & 5	Black	4 & 5
Shell	Drain & Shield	Shell

Notes:
Functionally equivalent components may be substituted

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	08/12/2019	Initial Release	Verified:	RoHS compliant	
			Dimensions are in millimeters.	Function test: no open, no short circuit, no intermittent	
			Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 1000 mm, 50-00580 USB A micro plug to same, 28 AWG, 30-00088 wire	
				Size: Part number: A 10-03396	
				Scale: 1:1	Sheet 1 of 1

5

4

3

2

1