 -Shell Plating : Passivated -Shell Plating : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +200°C -Sait Spray : 500 hours A 30-09-2016 First Release BASIC SERIES: 8D 7 11 K 98 N A 30-09-2016 First Release SHELL TYPE : Jam nut Receptacle - 11 K 98 N ONIGNITION I.N SCALE N		т		Q		П			ш		D		O
CHARACTERISTICS - Standard : Based on MIL-DT-38999 Series III - Shell Material ::::::::::::::::::::::::::::::::::::		B flat						S	ØA				
CHARACTERISTICS - Standard : Based on MIL-DT-38999 Series III - Shell Material ::::::::::::::::::::::::::::::::::::						Keying	Shown a	as example					
- Standard : Based on MIL-DTL-38999 Series III - Shell Material : Stainless Steel - Shell Plating : Passivated - Insulator : Thermoplastic - Contact S : Copper Alloy 0.8µm minimum - Ourability : 500 Mating cycles - Delivered with Souriau contacts and Accessories - Temperature Range : -65°C to +200°C - Salt Spray : 500 hours - Souriact Plating : 60°C to +200°C - Salt Spray : 500 hours - Timperature Range : -65°C to +200°C - Salt Spray : 500 hours - Souriact Plating : 00°C to +200°C - Salt Spray : 00°C to +200°C - Salt Spray : 00°C to +200°C - Salt Spray : 00°C to +200°C - Sal		CHARACTERISTICS				, .	F			-			
- Shell Material : Standard Crimp Contact Southau shallow - Shell Plating : Passivated R 32.5Max - Shell Plating : Copper Alloy S 31.80.04 - Contacts : Copper Alloy W 2.240.9/0.1 W the Specification (profe - Seals & Grommet : Silicon Elastomer - - M15x1-6g W 2.240.9/0.1 - Contact Plating : Gold over copper Alloy 0.8µm minimum - - M15x1-6g W 2.240.9/0.1 - Outact Plating : Gold over copper Alloy 0.8µm minimum -			IL-DTL-38999 Ser	ies III					Nominal				
-Temperature Range :: -65°C to +200°C -Salt Spray :: 500 hours BASIC SERIES: 8D 7 - 11 K 98 S N BASIC SERIES: 8D 7 - 11 K 98 S N SHELL TYPE :: Jam nut Receptacle CONTACT TYPE :: Standard Crimp Contact SHELL SIZE : 11 PLATING :: K = Passivated CONTACT LAYOUT :: 11:98 CONTACT SUBJECT CONTACT CONTACT CONTACT CONTACT LAYOUT :: 11:98 CONTACT CONTACT CO	2	-Shell Plating -Insulator -Contacts -Seals & Grommet -Contact Plating -Durability	 Passivated Thermoplastic Copper Alloy Silicon Elastom Gold over copp 500 Mating cyd 	ner per Alloy 0.8μm ι cles	ninimum			B R S W	19.07+0.1/-0.15 32.5Max 31.8±0.4 2.2+0.9/-0.1				SOURIAU shal due to a us the Specification (profes
-Salt Spray : 500 hours -Salt Spray : 500 hours A 30-09-2016 First Release ISS DATE Latest modifice Designed By: Date TITLE SCALE NA SCALE NA SOURIAU WWW CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 PLATING : K = Passivated CONTACT LAYOUT : 11-98 CONTACT LAYOUT : 11-98 CONTACT LAYOUT : 11-98													
BASIC SERIES: 8D 7 - 11 K 98 S N ITTLE BASIC SERIES: 8D 7 - 11 K 98 S N SHELL TYPE : Jam nut Receptacle ORIENTATION : N SCALE NA Image: Source of the second sec				-							A	30-09-2016	First Release
BASIC SERIES: 8D 7 - 11 K 98 S N SHELL TYPE : Jam nut Receptacle ORIENTATION : N SCALE NA CONTACT TYPE : Standard Crimp Contact ORIENTATION : N SOURIAU WWW SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 11-98 FORMAT													Latest modifica
BASIC SERIES. SD 7 - 11 K 98 3 N NA NA SHELL TYPE : Jam nut Receptacle ORIENTATION : N ORIENTATION : N NA SOURIAU WWV SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 11-98 FORMAT A3													
CONTACT TYPE : Standard Crimp Contact ORIENTATION : N SOURIAU WWV SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) FORMAT A3		BASIC SERIES:	80	0 7 -	11 K	98 S	Ν				SCA	LE	
SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) PLATING : K = Passivated FORMAT A3		SHELL TYPE : Jam nut F	Receptacle				L				NA		$\neg \Psi$
PLATING : K = Passivated FORMAT A3			dard Crimp Cont	act							SO	URIAU	WWV
A3								CONTAC				447	
		PLATING : K = P	assivated						CONTACT LAY	OUT : 11-98			
		н		G		F			F	1			C

 $\mathbf{\mathbf{n}}$

D		Þ						
				4				
LAYOUT SHOWN AS EXAMPLE								
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed PN: 8D711K98SN								
ation - by MOD N° te: CUSTOMER DRAWING								
Stainless Steel Receptacle 8D series General linear NPRDS / PROJECT Tolerances: 859 ± This document is the property of								
W.SOURIAU.COM SOURIAU it must not be reproduced or communicated without permission SOURIAU DRG N° SHEET								
8D711K98SN-		A	1/2					
I D		I A						

Г	D I	п	m		0		A	
4	$\begin{array}{c} \hline \\ \hline $			MAL	Panel cutout			4
	position ID X-axis (mm) Y-axis (mm) A +.000 (0.00) +.130 (3.30) B +.130 (3.30) +.000 (0.00) C +.065 (1.65) 113 (2.87) D 065 (1.65) 113 (2.87) E 130 (3.30) +.000 (0.00) F +.000 (0.00) +.000 (0.00) Shell Arrangement no. Number of contacts Size contacts Service rating Contact	Supersedes MS20050-98			ØC			
ى ت					Dim Nominal B 19.59+0/-0.25 ØC 20.96+0.25/-0			3
				1	SOURIAU shall not be liable for an due to a use of the Products wl the Specifications issued by either o (professional recommenda	nich does not comply with f the Parties or by a third party		
S					PN: 8D711	Not Listed		2
				A 30-09-2016 Fin ISS DATE Designed By: TITLE	Latest modification - by Date:	сизтомея двами eel Receptacle 8D series	MOD N° _	
-				SCALE NA SOURIAU	General linear Tolerances: ± WWW.SOURIAU.C	COM NPRDS / PROJECT 859 This document is th SOURIA it must not be rep communicated with	ne property of NU produced or	1
				FORMAT A3	SOURIAU 8D711K		SHEET 2/2	
_	H G	F	E	D	C	В	А	