	I	۵	П	т	τ	J	C	σ	A		_
4	R 22.6 Max	W pread		S			Image: constraint of the sector of the sec	HOWN AS EXAMPLE			4
N	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Ser -Shell Material : Aluminium -Shell Plating : Black Zinc Nick -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastom -Contact Plating : Gold over copp -Durability : 500 Mating cyde	el ner per Alloy 0.8μm minimur	Keying Shown a	s example Connector dimension Dim Nominal A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g			due to a use of the the Specifications issued		oly with a third party		2
	-Delivered with Souriau contacts and Act -Temperature Range <u>:</u> -65°C to +175° -Salt Spray : 500 hours -Mass : 17.99 g ± 10%	cessories °C				A 01-10-201 ISS DATE Designed By:	PN: 8	3D711Z04PN	CUSTOMER DRAWING	MOD N°	
						TITLE		uminium Receptacle			
_ _	BASIC SERIES:80SHELL TYPE : Jam nut ReceptacleCONTACT TYPE : Standard Crimp ContSHELL SIZE : 11		Z 04 P N	CONTACT TYPE : PIN(5)		SCALE NA SOURIAU			NPRDS / PROJECT 859 This document is the prop SOURIAU it must not be reproduc communicated without pe	ed or rmission	1
	PLATING : Z = Black Zinc Nickel	G	F	CONTACT LAY		FORMAT A3		URIAU DRG N° D711Z04PN-C B	A	SHEET 1/2	

Г	ت D	т (Г		₿ >	
4	$\underbrace{\text{Contact Layout}}_{-x_1} + x$		Panel cutout JAM NUT RECEPTACLE (TYPE 7)		4
	Contact position ID Contact location X-axis Y-axis Y-axis (mm) A +.065 (1.65) +.065 (1.65) B +.065 (1.65) 065 (1.65) C 065 (1.65) 065 (1.65) D 065 (1.65) +.065 (1.65) Shell size Arrangement no. Number of contacts Size contacts Service rating Contact Supersedes 11 -4 4 20 I All MS20050-4		Dim Nomir		
ω			B 19.59+0/ ØC 20.96+0.2	-0.25	3
			due to a use of the P the Specifications issued	able for any non-conformity or damage Products which does not comply with by either of the Parties or by a third party commendation, technical notice.)	
N				Country Jurisdiction & Control List FR Not Listed	2
			A 01-10-2016 First Release ISS DATE Latest modification - by	MOD	N°
			Designed By: Date:	CUSTOMER DRAWING	
			TITLE Alu	uminium Receptacle 8D series	
<u> </u>				eral linear lerances: ± This document is the property of SOURIAU	1
			SOURIAU WWW.SOU	KIAU.COIVI it must not be reproduced or communicated without permission	
				URIAU DRG N° SHEE 0711Z04PN-C 2/2	
L	H G	FE		B A	
			,		