


C410C471J3G5TA

AxiMax 400 Comm COG, Ceramic, 470 pF, 5%, 25 VDC, COG, AxiMax, Commercial Standard



General Information	
Series	AxiMax 400 Comm C0G
Description	AxiMax, Commercial Standard
RoHS	Yes
Termination	Tin
AEC-Q200	No
Halogen Free	Yes

Specifications	
Capacitance	470 pF
Measurement Condition	1 MHz 1.0Vrms
Capacitance Tolerance	5%
Voltage DC	25 VDC
Dielectric Withstanding Voltage	62.5 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	COG
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	30PPM/C, 1MHz 1.0Vrms
Dissipation Factor	0.1% 1 MHz 1.0Vrms
Aging Rate	0% Loss/Decade Hour
Insulation Resistance	100 GOhms

Click here for the 3D model.

D 2.41mm MAX L 4.32mm MAX LL 25.4mm MIN F 0.51mm +0.025/-0.076mm	Dimensions	
LL 25.4mm MIN	D	2.41mm MAX
	L	4.32mm MAX
F 0.51mm +0.025/-0.076mm	LL	25.4mm MIN
	F	0.51mm +0.025/-0.076mm

Packaging Specifications	,
Packaging	Bulk, Bag
Packaging Quantity	300

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.