

Specification Sheet

Part Number: 150-45397



Standoff Bundling Clip, 1.6" Long, Panel Thickness .02"-.07", PA66HIRHS, Black, 500/box

| | |
|---------------------|--|
| Article Number | 150-45397 |
| Type | STAND OFF CLIP |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">•Clip can be installed by hand – no need for hardware or tools.•Design provides low insertion and high extraction force, for simple, secure performance.•Clip keeps bundle away from areas that could cause damage due to rubbing. |
| Quantity Per | bag |

Product Description

Standoff bundling clips provide a straightforward way to secure cable bundles, hoses or pipes. The bundle fastens to the tape bar using tape or cable ties. Multiple orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standoff keeps bundles away from mounting area to prevent them from damage due to rubbing.

| | |
|--|---|
| Short Description | Standoff Bundling Clip, 1.6" Long, Panel Thickness .02"-.07", PA66HIRHS, Black, 500/box |
| Global Part Name | STAND OFF CLIP-PA66HIRHS-BK |
| Length L (Imperial) | 1.6 |
| Length L (Metric) | 40.0 |
| Offset Length(Imperial) | 1.22 |
| Offset Length(Metric) | 31.0 |
| Fixation Method | Arrowhead |
| Height H (Imperial) | 0.6 |
| Height H (Metric) | 15.24 |
| Panel Thickness Min(Imperial) | 0.02 |
| Panel Thickness Max(Imperial) | 0.06 |
| Panel Thickness Min (Metric) | 0.4 |
| Panel Thickness Max (Metric) | 1.6 |
| Mounting Hole Diameter D (Imperial) | 0.26 - 0.27 |
| Mounting Hole Diameter D (Metric) | 6.5 - 6.8 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.28 |

| | |
|--|------|
| Mounting Hole Diameter D Max (Imperial) | 0.27 |
|--|------|

| | |
|--|-----|
| Mounting Hole Diameter D Max (Metric) | 6.8 |
|--|-----|

| | |
|------------------------------|------|
| Disc Diameter(Metric) | 18.0 |
|------------------------------|------|

| | |
|---------------------------------|------|
| Disc Diameter (Imperial) | 0.71 |
|---------------------------------|------|

| | |
|-----------------|--|
| Material | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
|-----------------|--|

| | |
|--------------------------|-----------|
| Material Shortcut | PA66HIRHS |
|--------------------------|-----------|

| | |
|---------------------|----------|
| Flammability | UL 94 HB |
|---------------------|----------|

| | |
|---------------------------------------|-----------------------------------|
| Operating Temperature (Metric) | -40°F to +221°F (-40°C to +105°C) |
|---------------------------------------|-----------------------------------|

| | |
|------------------------------------|-----|
| Reach Complaint(Article 33) | Yes |
|------------------------------------|-----|

| | |
|-----------------------|-----|
| ROHS Complaint | Yes |
|-----------------------|-----|

| | |
|-----------------------------------|-----|
| Package Quantity(Imperial) | 500 |
|-----------------------------------|-----|

| | |
|----------------------------------|-----|
| Package Quantity (Metric) | 500 |
|----------------------------------|-----|

| | |
|-----------------------|------------|
| Customs Number | 3926909988 |
|-----------------------|------------|

| | |
|-----------------------------|------|
| Content Unit(BMEcat) | pcs. |
|-----------------------------|------|

| | |
|------------------------|-------|
| Weight (Metric) | 1.825 |
|------------------------|-------|

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)