



.XXX ±0.05

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER	
ORIGINAL	1






NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED




OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	50Ω (IMPEDANCE)	_
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.	Ó
	5000MO min	


INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

 $5000M\Omega$ min.

1000V AC rms



		SW REFERENCE NO.: 629 COMBO ASSEMBLY						
	COMBINATION D-SUB			DRAWN: C.B		DATE: JAN. 01/2019		19
				CHECKED:		DATE:		
	EDAC INC TORONTO, ONTARIO CANADA	EDAC INC	OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS	SCALE: (IN C.A.D. 1	l:1)	SHEET 1	OF	2
		TORONTO, ONTARIO CANADA		DRAWING NUMBER: 629-17W224		2240-5TE		ISSUE
	YOUR CONNECTION TO	QUALITY & SERVICE		PART NUMBER:	629-17W	2240-5TE		1





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

