

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER. .X ±0.25




| ISSUE NUMBER |     |
|--------------|-----|
| ORIGINAL     | (1) |





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

COMPLIANT



NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED

**OPERATING TEMPERATURE:** -55°C ~ 125°C POWER/CO-AX CONTACT RATING:


.XX ±0.13 .XXX ±0.05

(IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.

**INSULATOR RESISTANCE:** DIELECTRIC WITHSTANDING VOLTAGE: 10A (CURRENT)

5000MΩ min.

1000V AC rms



|                            |  |  |                         | SW REFERENCE NO.: 629 COMBO ASSEMBLY |                |       |  |
|----------------------------|--|--|-------------------------|--------------------------------------|----------------|-------|--|
| COM                        | COMBINATION D-SUB  |  | DRAWN:                  | C.B                                  | DATE: JAN. 01/ | 2019  |  |
|                            |  |  | CHECKED:                |                                      | DATE:          |       |  |
|                            | EDAG INC<br>TORONTO, ONTARIO<br>YOUR CONNECTION TO QUALITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND<br>SHALL NOT BE REPRODUCED,OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | SCALE:                  | (IN C.A.D. 1:1)                      | SHEET 1 O      | = 2   |  |
|                            |  |  | DRAWING NUMBER: 629-3W3 |                                      | -240-1N3       | ISSUE |  |
| YOUR CONNECTION TO QUALITY |  |  | PART NUM                | IBER: 629-3W3                        | -240-1N3       | 1     |  |

