

SITOP BAT8600/PB/380WH

SITOP BAT8600 Pb battery module for UPS8600 DC 48 V/380 Wh energy storage: mainten.-free lead batteries



Output	
energy content of energy storage	380 W·h
output current rated value	20 A
output voltage at DC rated value	48 V
number of parallel-switched equipment resources for increasing the power	5
Safety	
design of short-circuit protection	Blade-type fuse 40 A, 58 V DC
design of the overload protection	Valve control
Safety	
operating resource protection class	Class III
protection class IP	IP20
Approvals	
certificate of suitability	
<ul style="list-style-type: none"> • CE marking • UL approval • as approval for USA 	Yes Yes cURus-Recognized (UL 1778, CSA C22.2 No. 107.1), File E219627; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
<ul style="list-style-type: none"> • CSA approval • cCSAus, Class 1, Division 2 • ATEX 	Yes No No
type of certification CB-certificate	Yes
certificate of suitability	
<ul style="list-style-type: none"> • EAC approval • shipbuilding approval 	Yes Yes
shipbuilding approval	ABS, DNV GL
Marine classification association	
<ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • DNV GL 	Yes Yes
environmental conditions	
Operating data note	For storage, mounting and operation of batteries, the relevant DIN/VDE regulations or country-specific regulations (e.g. VDE 0510 Part 2/EN 50272-2) must be observed.
ambient temperature	
<ul style="list-style-type: none"> • during operation • during transport • during storage 	-10 ... +50 °C -40 ... +60 °C -15 ... +40 °C
Service life	
service life of energy storage	
<ul style="list-style-type: none"> • typical 	capacity falls to 80 % of original capacity (according to EUROBAT)

<ul style="list-style-type: none"> • at 20 °C typical • at 30 °C typical • at 40 °C typical • at 50 °C typical 	<p>4 y</p> <p>2 y</p> <p>1 y</p> <p>0.5 y</p>
ambient temperature during storage	In addition to the storage temperature, additional factors, such as storage duration and charging status during storage, have a major impact on the potential service life. This means batteries should preferably be stored fully charged for short periods of time in a dry, cool and frost-proof (temperature range 0 to +20 °C) location.
Mechanics	
type of electrical connection <ul style="list-style-type: none"> • for power supply unit 	Plug-in terminals with screwed connection +, -: 2 plug-in terminals with 1 screwed connection each for 0.2 ... 10 mm ²
product component included	2x blade-type fuse 40 A, 58 V DC
width of the enclosure	322 mm
height of the enclosure	187 mm
depth of the enclosure	110 mm
installation width	322 mm
mounting height	207 mm
required spacing <ul style="list-style-type: none"> • top • bottom • left • right 	20 mm 0 mm 0 mm 0 mm
fastening method <ul style="list-style-type: none"> • wall mounting • standard rail mounting • S7 rail mounting 	Yes No No
fastening method	Keyhole mounting for hooking in to M4 screws
net weight	13.5 kg
number of batteries	4
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

