## **ON Semiconductor®**



Title of Change:	Wafer	Wafer diameter change from 5inch Bucheon to 6inch Bucheon				
Proposed First Ship date:	18 Dec	18 Dec 2020 or earlier if approved by customer				
Contact Information:	Contac	Contact your local ON Semiconductor Sales Office or Yuna.Im@onsemi.com				
PCN Samples Contact:	Sample Initial F Sample	Contact your local ON Semiconductor Sales Office or <pcn.samples@onsemi.com>. Sample requests are to be submitted no later than 30 days from the date of first notification, Initial PCN or Final PCN, for this change. Samples delivery timing will be subject to request date, sample quantity and special customer packing/label requirements.</pcn.samples@onsemi.com>				
Additional Reliability Data:	Contac	Contact your local ON Semiconductor Sales Office or songyong.sim@onsemi.com				
Type of Notification:	90 days ON Ser	This is a Final Product/Process Change Notification (FPCN) sent to customers. FPCNs are issued 90 days prior to implementation of the change. ON Semiconductor will consider this change accepted, unless an inquiry is made in writing within 30 days of delivery of this notice. To do so, contact PCN.Support@onsemi.com				
Marking of Parts/ Traceability of Change:	Lot cod	Lot code 2020 year.				
Change Category:	Wafer	Wafer Fab Change				
Change Sub-Category(s):	Wafer	Wafer diameter changes from 5inch to 6inch and adding passivation				
Sites Affected:						
ON Semiconductor Sites			External Foundry/Subcon Sites			
ON Semiconductor Bucheon, Korea			None			
<b>Description and Purpose:</b> Supply enhancement due to Bucheon 5inch	fab closure	instead EOL pro	ducts. Qfet is qualified tech	in Bucheon 6inch.		
Item		Before Change Description		After Change Description		
Wafer diameter			Bucheon 5inch	Bucheon 6inch		
Passivation	No		Nitride passivation			

## **ON Semiconductor®**



#### **Reliability Data Summary:**

QV DEVICE NAME: FQP2N40-F080 RMS: K70179, K70446 PACKAGE: TO220

Test	Specification	Condition	Interval	Results	
HTRB	JESD22-A108	Tj=150°C, 80% max rated V	1008 hrs	0/240	
HTGB	JESD22-A108	Tj=150°C, 100% max rated Vgss	1008 hrs	0/240	
HTSL	JESD22-A103	Ta=150°C	1008 hrs	0/240	
IOL	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 3.5 min	8572 cyc	0/120	
TC	JESD22-A104	Ta= -55°C to +150°C	1000 cyc	0/120	
H3TRB	JESD22-A110	130°C, 85% RH, 18.8psig, bias (100V)	1008 hrs	0/120	
uHAST	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs	0/120	

### **Electrical Characteristics Summary:**

Electrical characteristics are not impacted.

### List of Affected Parts:

**Note:** Only the standard (off the shelf) part numbers are listed in the parts list. Any custom parts affected by this PCN are shown in the customer specific PCN addendum in the PCN email notification, or on the **PCN Customized Portal**.

Part Number	Qualification Vehicle
FQP2N40-F080	FQP2N40-F080

# Appendix A: Changed Products

D

Product	Customer Part Number	Qualification Vehicle	New Part Number	Replacement Supplier
FQP2N40-F080		FQP2N40-F080		