ATGBICS FTLX3671DTC60 Finisar Compatible Transceiver DWDM Ch60 SFP+ 1.2 to 11.3GBase (1529.55nm, SMF, 40km, LC, DOM, Ind Temp)

Brand : ATGBICS

Product name : FTLX3671DTC60 Finisar Compatible Transceiver DWDM Ch60 SFP+ 1.2 to 11.3GBase (1529.55nm, SMF, 40km, LC, DOM, Ind Temp)

FTLX3671DTC60 Finisar Compatible Transceiver DWDM Ch60 SFP+ 1.2 to 11.3GBase (1529.55nm, SMF, 40km, LC, DOM, Ind Temp)


ATGBICS FTLX3671DTC60 Finisar Compatible Transceiver DWDM Ch60 SFP+ 1.2 to 11.3GBase (1529.55nm, SMF, 40km, LC, DOM, Ind Temp). SFP transceiver type: Fiber optic, Maximum data transfer rate: 10000 Mbit/s, Interface type: SFP+. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 3.5 V, Power consumption (typical): 1 W. Width: 13.4 mm, Depth: 56.5 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box





Performance		Power	
SFP transceiver type *Fiber opticMaximum data transfer rate *10000 Mbit/sInterface type *SFP+Single-mode fiber (SMF) supported✓Multi-mode fiber (MMF) supportedXFiber optic connectorLCSFP transceiver standardDWDMMaximum transfer distance40000 mWavelength1529.55 nmCoarse Wavelength Division Multiplexing (CWDM)✓Ethernet LAN✓	10000 Mbit/s SFP+	Input voltage Maximum voltage Power consumption (typical) Operational conditions	3.3 V 3.5 V 1 W
	LC DWDM 40000 m 1529.55 nm	Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-40 °C 85 °C -40 - 85 °C -40 - 85 °C 0 - 95% 0 - 95%
	<	Weight & dimensions	
Ethernet interface type Digital Diagnostics Monitoring (DDM)	10 Gigabit Ethernet 🗸	Width Depth Height	13.4 mm 56.5 mm 8.5 mm
Features		Weight	19 g
Product colour	Silver Metal	Packaging data	
Housing material Metal Plug and Play Hot-swap	4	Number of products included Package type	l pc(s) Box
Easy to install	•	Technical details	
Country of originUnited KingdomBrand compatibilityFinisarCertificationCE, FCC, RoHS	Sustainability compliance Sustainability certificates Doesn't contain	✔ RoHS Lead	

Product code: FTLX3671DTC60-C



5056468764362

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.