

Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

SmartRack Premium 55U Standard-Depth Rack Enclosure Cabinet

MODEL NUMBER: SR55UB











Extra-tall 55U cabinet houses, organizes and secures standard-depth 19 in. rack equipment in high-density server and IT networking areas.

Features

Standard-Depth 55U Server Cabinet Accommodates 19 in. Rack Equipment

This SmartRack® 55U rack enclosure is designed for network wiring closets, retail locations, classrooms, back offices and other areas with essential rack-mount IT equipment. Constructed from heavy-duty steel with a durable black powder-coated finish, the SR55UB has a maximum stationary load capacity of 3000 pounds (1363 kilograms) and a maximum rolling load capacity of 2250 pounds (1022 kilograms).

Exceptional 55U Height Lets You Make the Best Use of Valuable Floor Space

The extra height allows you to stack more equipment vertically and make optimal use of available floor space. This 55U rack cabinet has a footprint of 24 inches (600 millimeters) wide and 43 inches (1092 millimeters) deep.

Keeps Important Equipment Secure

The reversible front door, split rear doors and half-size side panels lock securely to help prevent damage, tampering or theft. The doors, side panels and top panel are designed for quick release, making it easy to access connected equipment and cabling with little effort. Convenient top access ports and an open bottom allow easy cable routing through the cabinet. The vented doors allow generous airflow (more than 65% open space) from front to rear to keep your equipment cool and functioning at their peak.

Easy Enclosure and Equipment Installation

This 55U server rack comes fully assembled for quick and easy deployment with pre-installed (and removable) casters that let you maneuver it over a level, smooth, stable surface and through a standard seven-foot (2.1-meter) doorway into position, where it can be stabilized by adjusting the levelers (also removable). Front and rear mounting rails accept standard rack equipment up to 37 inches (940 millimeters) deep. Toolless 0U mounting rails allow quick installation of up to four compatible PDUs and vertical cable managers.

Designed for Baying Multiple Enclosures in a Row

Built-in baying tabs allow the combination of two or more rack cabinets in a row. Center-to-center width can be set at 24 inches (600 millimeters) to match standard data center floor tiles.

Meets Payment Card Industry Standards

The SR55UB provides physical equipment and media security required for PCI DSS (Payment Card

Highlights

- Maximum capacity: 3000 lb. (1363 kg) stationary, 2250 lb. (1022 kg) rolling load
- Doors and side panels lock securely to help prevent damage, tampering or theft
- Ships fully assembled for immediate deployment and equipment mounting
- Provides physical equipment and media security required for PCI DSS compliance

Applications

Store and organize rack-mount equipment in a network closet, data center or other area where you need components to be secure

Package Includes

- SR55UB 55U Server Rack
- (4) Side panels
- (4) Side panel locks
- (2) Keys
- (50) M6 screws
- (50) M6 washers
- (50) M6 cage nuts
- Owner's manual



Industry Data Security Standard) compliance. This is essential for companies that process, store and/or transmit credit card information.

Specifications

Device Compatibility Network Switch; PDU; Patch Panel; Router; Server; UPS Rack Type Enclosure; Floor-Standing PHYSICAL Color Black Factory Preset Rack Depth (in.) 27.75 Factory Preset Rack Depth (cm) 70.5 Factory Preset Rack Depth (rm) 39.98 Maximum Device Depth (in.) 37 Maximum Device Depth (in.) 34 Minimum Device Depth (in.) 4 Minimum Device Depth (in.) 10.2 Rack Height 55U Shipping Dimensions (hwd / cm.) 267.97 x 65.40 x 115.57 Shipping Dimensions (hwd / in.) 105.50 x 25.75 x 45.50 Shipping Weight (lbs.) 40.50 Unit Dimensions (hwd / cm.) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / in.) 101.180 x 23.622 x 43.000 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (kg) 1,021	-	
Device Compatibility Network Switch; PDU; Patch Panel; Router; Server; UPS Rack Type Enclosure; Floor-Standing PHYSICAL Color Black Factory Preset Rack Depth (in.) 27.75 Factory Preset Rack Depth (cm) 70.5 Factory Preset Rack Depth (rm) 39.98 Maximum Device Depth (in.) 37 Maximum Device Depth (in.) 34 Minimum Device Depth (in.) 4 Minimum Device Depth (in.) 10.2 Rack Height 55U Shipping Dimensions (hwd / cm.) 267.97 x 65.40 x 115.57 Shipping Dimensions (hwd / in.) 105.50 x 25.75 x 45.50 Shipping Weight (lbs.) 40.50 Unit Dimensions (hwd / cm.) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / in.) 101.180 x 23.622 x 43.000 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (kg) 1,021	OVERVIEW	
Rack Type Enclosure; Floor-Standing PHYSICAL Color Black Factory Preset Rack Depth (m.) 27.75 Factory Preset Rack Depth (rm) 70.5 Factory Preset Rack Depth (mm) 705 Maximum Device Depth (mn) 33.98 Maximum Device Depth (in.) 37 Maximum Device Depth (mm) 940 Minimum Device Depth (mm) 10.16 Minimum Device Depth (mm) 102 Rack Height 55U Shipping Dimensions (hvd / cm) 267.97 x 65.40 x 115.57 Shipping Weight (kg) 195.27 Shipping Weight (kg) 195.27 Shipping Weight (kg) 430.50 Unit Dimensions (hvd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hvd / in.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (kg) 170.12 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (kg) 3,361 </th <th>UPC Code</th> <th>037332260789</th>	UPC Code	037332260789
PHYSICAL Color Black Factory Preset Rack Depth (in.) 27.75 Factory Preset Rack Depth (cm) 70.5 Factory Preset Rack Depth (mm) 93.98 Maximum Device Depth (in.) 37 Maximum Device Depth (in.) 940 Minimum Device Depth (in.) 4 Minimum Device Depth (in.) 4 Minimum Device Depth (in.) 4 Minimum Device Depth (in.) 102 Rack Height 55U Shipping Dimensions (hwd / cm) 267.97 x 65.40 x 115.57 Shipping Dimensions (hwd / in.) 105.50 x 25.75 x 45.50 Shipping Weight (kg) 195.27 Shipping Weight (lbs.) 430.50 Unit Dimensions (hwd / in.) 101.18 x 23.622 x 43.000 Unit Dimensions (hwd / in.) 101.18 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (ks) 1,021 Weight Capacity - Stationary (ks) 1,361 Weight Capacity - Stationary (ks)	Device Compatibility	Network Switch; PDU; Patch Panel; Router; Server; UPS
Color Black Factory Preset Rack Depth (in.) 27.75 Factory Preset Rack Depth (cm) 70.5 Factory Preset Rack Depth (cm) 93.98 Maximum Device Depth (in.) 37 Maximum Device Depth (mm) 940 Minimum Device Depth (cm) 10.16 Minimum Device Depth (in.) 4 Minimum Device Depth (in.) 4 Minimum Device Depth (in.) 102 Rack Height 55U Shipping Dimensions (hwd / cm) 267.97 x 65.40 x 115.57 Shipping Weight (kg) 195.27 Shipping Weight (libs.) 430.50 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Weight (kg) 170.12 Unit Weight (kg) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (libs.) 250 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (kg) 1,361	Rack Type	Enclosure; Floor-Standing
Factory Preset Rack Depth (in) 70.5 Factory Preset Rack Depth (inm) 705 Maximum Device Depth (inm) 93.98 Maximum Device Depth (inm) 37 Maximum Device Depth (inm) 940 Minimum Device Depth (inm) 10.16 Minimum Device Depth (inm) 4 Minimum Device Depth (inm) 102 Rack Height 55U Shipping Dimensions (hwd / cm) 267.97 x 65.40 x 115.57 Shipping Weight (kg) 195.27 Shipping Weight (kg) 195.27 Shipping Weight (kg) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Weight (kg) 170.12 Unit Weight (kg) 170.12 Unit Weight (kg) 1,021 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (kg) 3000 Rack Depth Standard	PHYSICAL	
Factory Preset Rack Depth (cm) 70.5 Factory Preset Rack Depth (cm) 93.98 Maximum Device Depth (in.) 37 Maximum Device Depth (cm) 940 Minimum Device Depth (cm) 10.16 Minimum Device Depth (in.) 4 Minimum Device Depth (mm) 102 Rack Height 55U Shipping Dimensions (hwd / cm) 267.97 x 65.40 x 115.57 Shipping Dimensions (hwd / in.) 105.50 x 25.75 x 45.50 Shipping Weight (kg) 195.27 Shipping Weight (kg) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Weight (kg) 170.12 Unit Weight (kg) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (kg) 1,361 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (kg) 5tandard	Color	Black
Factory Preset Rack Depth (mm) 705 Maximum Device Depth (in.) 93.98 Maximum Device Depth (in.) 37 Maximum Device Depth (mm) 940 Minimum Device Depth (in.) 10.16 Minimum Device Depth (in.) 4 Minimum Device Depth (mm) 102 Rack Height 55U Shipping Dimensions (hwd / cm) 267.97 x 65.40 x 115.57 Shipping Dimensions (hwd / in.) 105.50 x 25.75 x 45.50 Shipping Weight (kg) 195.27 Shipping Weight (ibs.) 430.50 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / rin.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (kg) 1,021 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth 5tandard	Factory Preset Rack Depth (in.)	27.75
Maximum Device Depth (cm) 93.98 Maximum Device Depth (in.) 37 Maximum Device Depth (mm) 940 Minimum Device Depth (cm) 10.16 Minimum Device Depth (in.) 4 Minimum Device Depth (mm) 102 Rack Height 55U Shipping Dimensions (hwd / cm) 267.97 x 65.40 x 115.57 Shipping Dimensions (hwd / in.) 105.50 x 25.75 x 45.50 Shipping Weight (kg) 195.27 Shipping Weight (lbs.) 430.50 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / rin.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (kg) 1,021 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Factory Preset Rack Depth (cm)	70.5
Maximum Device Depth (in.) 37 Maximum Device Depth (mm) 940 Minimum Device Depth (cm) 10.16 Minimum Device Depth (in.) 4 Minimum Device Depth (mm) 102 Rack Height 55U Shipping Dimensions (hwd / cm) 267.97 x 65.40 x 115.57 Shipping Dimensions (hwd / in.) 105.50 x 25.75 x 45.50 Shipping Weight (kg) 195.27 Shipping Weight (lbs.) 430.50 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / in.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (kg) 1,361 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Factory Preset Rack Depth (mm)	705
Maximum Device Depth (mm) 940 Minimum Device Depth (cm) 10.16 Minimum Device Depth (in.) 4 Minimum Device Depth (mm) 102 Rack Height 55U Shipping Dimensions (hwd / cm) 267.97 x 65.40 x 115.57 Shipping Dimensions (hwd / in.) 105.50 x 25.75 x 45.50 Shipping Weight (kg) 195.27 Shipping Weight (lbs.) 430.50 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / in.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (kg) 1,361 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Maximum Device Depth (cm)	93.98
Minimum Device Depth (cm) 10.16 Minimum Device Depth (in.) 4 Minimum Device Depth (mm) 102 Rack Height 55U Shipping Dimensions (hwd / cm) 267.97 x 65.40 x 115.57 Shipping Dimensions (hwd / in.) 105.50 x 25.75 x 45.50 Shipping Weight (kg) 195.27 Shipping Weight (lbs.) 430.50 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / in.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (lbs.) 2250 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Maximum Device Depth (in.)	37
Minimum Device Depth (in.) 4 Minimum Device Depth (mm) 102 Rack Height 55U Shipping Dimensions (hwd / cm) 267.97 x 65.40 x 115.57 Shipping Dimensions (hwd / in.) 105.50 x 25.75 x 45.50 Shipping Weight (kg) 195.27 Shipping Weight (lbs.) 430.50 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / in.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (lbs.) 2250 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Maximum Device Depth (mm)	940
Minimum Device Depth (mm) 102 Rack Height 55U Shipping Dimensions (hwd / cm) 267.97 x 65.40 x 115.57 Shipping Dimensions (hwd / in.) 105.50 x 25.75 x 45.50 Shipping Weight (kg) 195.27 Shipping Weight (lbs.) 430.50 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / in.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (lbs.) 2250 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Minimum Device Depth (cm)	10.16
Rack Height 55U Shipping Dimensions (hwd / cm) 267.97 x 65.40 x 115.57 Shipping Dimensions (hwd / in.) 105.50 x 25.75 x 45.50 Shipping Weight (kg) 195.27 Shipping Weight (lbs.) 430.50 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / in.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Minimum Device Depth (in.)	4
Shipping Dimensions (hwd / cm) 267.97 x 65.40 x 115.57 Shipping Dimensions (hwd / in.) 105.50 x 25.75 x 45.50 Shipping Weight (kg) 195.27 Shipping Weight (lbs.) 430.50 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / in.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (lbs.) 2250 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Minimum Device Depth (mm)	102
Shipping Dimensions (hwd / in.) 105.50 x 25.75 x 45.50 Shipping Weight (kg) 195.27 Shipping Weight (lbs.) 430.50 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / in.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (lbs.) 2250 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Rack Height	55U
Shipping Weight (kg) 195.27 Shipping Weight (lbs.) 430.50 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / in.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (lbs.) 2250 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Shipping Dimensions (hwd / cm)	267.97 x 65.40 x 115.57
Shipping Weight (lbs.) 430.50 Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / in.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (lbs.) 2250 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Shipping Dimensions (hwd / in.)	105.50 x 25.75 x 45.50
Unit Dimensions (hwd / cm) 257.00 x 60.00 x 109.22 Unit Dimensions (hwd / in.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (lbs.) 2250 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Shipping Weight (kg)	195.27
Unit Dimensions (hwd / in.) 101.180 x 23.622 x 43.000 Unit Weight (kg) 170.12 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (lbs.) 2250 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Shipping Weight (lbs.)	430.50
Unit Weight (kg) 170.12 Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (lbs.) 2250 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Unit Dimensions (hwd / cm)	257.00 x 60.00 x 109.22
Unit Weight (lbs.) 375.050 Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (lbs.) 2250 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Unit Dimensions (hwd / in.)	101.180 x 23.622 x 43.000
Weight Capacity - Rolling (kg) 1,021 Weight Capacity - Rolling (lbs.) 2250 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Unit Weight (kg)	170.12
Weight Capacity - Rolling (lbs.) 2250 Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Unit Weight (lbs.)	375.050
Weight Capacity - Stationary (kg) 1,361 Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Weight Capacity - Rolling (kg)	1,021
Weight Capacity - Stationary (lbs.) 3000 Rack Depth Standard	Weight Capacity - Rolling (lbs.)	2250
Rack Depth Standard	Weight Capacity - Stationary (kg)	1,361
	Weight Capacity - Stationary (lbs.)	3000
Number of Vertical Mounting Rails 4	Rack Depth	Standard
Trainbol of Voluda invarially Italia	Number of Vertical Mounting Rails	4



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

FEATURES & SPECIFICATIONS		
Grounding Lug	Front and back door frames	
Built-in Cable Management	Yes	
Extra Wide	No	
STANDARDS & COMPLIANCE		
Certifications	UL60950; RoHS; CE; IP20 Protection Rating	
Approvals	EIA/ECA-310-E	
WARRANTY		
Product Warranty Period (Worldwide)	5-year limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies