

## F461JT683K250L

Not for New Design

F461, Film, Metallized Polypropylene, General Purpose, 0.068 uF, 10%, 250 VDC, 85°C, Lead Spacing = 5mm



### General Information

|                  |   |
|------------------|---|
| Series           | F461  |
| Dielectric       | Metallized Polypropylene  |
| Style            | Radial  |
| Features         | MKP, Pulse  |
| RoHS             | Yes   |
| Lead             | Wire Leads  |
| AEC-Q200         | No  |
| Component Weight | 1.733 g   |
| Miscellaneous    | The Rated Voltage Decreases 2%/C Between +85C And +105C (1.25%/C For AC). ClimCat: 55/105/56. |
| Notes            | Series Replaced by R75.   |

Click [here](#) for the 3D model.

### Dimensions

|                |                 |
|----------------|-----------------|
| L              | 7.2mm -0.5mm    |
| H              | 11mm -0.5mm     |
| T              | 6mm -0.5mm      |
| S              | 5mm +0.6/-0.1mm |
| H <sub>0</sub> | 18.5mm +/-0.5mm |
| F              | 0.5mm +/-0.05mm |
| G              | 0.5mm NOM       |

### Packaging Specifications

|                    |      |
|--------------------|------|
| Packaging          | T&R  |
| Packaging Quantity | 1000 |

### Specifications

|                       |                                       |
|-----------------------|---------------------------------------|
| Capacitance           | 0.068 uF                              |
| Capacitance Tolerance | 10%                                   |
| Voltage AC            | 160 VAC                               |
| Voltage DC            | 250 VDC, 150 VDC (105C)               |
| Temperature Range     | -55/+105°C                            |
| Rated Temperature     | 85°C                                  |
| Dissipation Factor    | 0.04% 1kHz, 0.06% 10kHz, 0.25% 100kHz |
| Insulation Resistance | 100 GOhms                             |
| Max dV/dt             | 250 V/us                              |
| Inductance            | 6 nH                                  |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.