


## L8040C1R4NDWDT

Aliases (L8040C1R4NDWDT)

Not for New Design • Scheduled EOL - Last date to buy 30 JUN 2023 KEMET, L-DWD, Power, 1.4 uH, 20%, 8040(3131)



General Information		
Series	L-DWD	
Style	SMD	
Chip Size	8040(3131)	
Description	Shielded, Surface Mount Inductor	
Features	Low Profile	
RoHS	Yes	
Notes	Last Order Date June 30, 2023. Suggested Replacement - https://www.chilisin.com/en- global/Inductor/Product/BWVS_808040/BWVS008080401R4T00.	

Click here for the 3D model.

Dimensions		
L	8mm +/-0.2mm	
W	8mm +/-0.2mm	
Т	4.2mm MAX	
S	5.6mm +/-0.3mm	
LL	1.6mm +/-0.3mm	

Packaging Specifications			
Packaging	T&R		
Packaging Quantity	1000		

Specifications			
Inductance	1.4 uH		
Inductance Tolerance	20%		
Temperature Range	-25/+120°C		
Shielded	Yes		
Current	7000 mAmps (MAX)		
DC Resistance	0.007 Ohms		
Self-Resonant Frequency	63 MHz		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.