

6	5	4	3	2	1	

Physical	
Dimensions	45.97mm x 7.62mm x 1.57mm (1.81" x 0.30" x 0.062")
Use Case	On metal
Attachment	High performance acrylic adhesive, 3M 300 LSE, others available on request
Weight	1.5 grams

J

Ι

Н

G

F

Е

D

С

Electrical/RF						
Typical Read Range	8-9 feet at 36 dBm ERP, on cable					
Frequency	902-928 MHz					
IC Platform	Alien Higgs3					
IC Memory	96 bit EPC 512-bit user memory					

Environmental						
Classification	IP67					
Operating Temperature	-50°C to +85°C (-58° to +185°F)					
Temperature Tolerance	-50°C to +185°C (-58° to +365°F)					
Steel Ball Drop Test	18" drop with 1" diameter steel ball					

1. HEIGHT DIMENSION DOES NOT INCLUDE ADHESIVE.

								1				
RAL TOLERANCES			DIMENSION STYLE		SCALE	DES	IGN UNITS) ANGLE		
LESS SPECIFIED)		IN/MM		4:1				PROJ	ECTION	В		
	mm	INCH	DRAWN		DATE	TITLE		П				
S	±	±	MMALONE 2019/02/06 RFID									
S	±	±.010	CHECKED BY DATE				SALES DRAWING					
S	±.25	±.030]			-		-				
E	±.76	±	APPROVED BY DATE		molex	molex MOLEX INCORPORATED						
ANGULAR ±1/2°			GLISH	2019/03/0					JNAT	LD		
RAFT WHERE ▲ APPLICABLE		MATERI	MATERIAL NO. 133561351			DOCUMENT NO. SD-13356-1351					A	
AUST REMAIN HIN DIMENSIONS			C SIZE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION								
6 5				4	3		2			1	\searrow	