4		Z	ØS							
ယ							LAYOUT SHO	OWN AS EXAMPLE		
			Keying Shov	wn as example						
c	CHARACTERISTICS			Connector dimension	-					
-5	-Standard : Based on I	MIL-DTL-38999 Series III		Dim Nominal						
-S -Ir -C	-Shell Material: AluminiumØS25 Max-Shell Plating: Olive drab CadmiumZ31 Max-Insulator: ThermoplasticVV THREADM15x1-6g-Contacts: Copper AlloySeals & Grommet: Silicon Elastomer					SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
<b>⊳</b> -C	-Contact Plating	: Gold over copper Alloy 0.8µm min	iimum					FR	Not Listed	
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories					PN: 8D511W05SB				
	-Temperature Range	: -65°C to +175°C				A 17-10-20	16 First Release			
	-Salt Spray	: 500 hours								
N	-Mass	: 18.04 g ± 10%				ISS DATE Designed By:	Latest modification - by Date:		CUSTOMER DRAWING	DD N°
						TITLE Aluminium Plug 8D se		D series	ries	
	BASIC SERIES: SHELL TYPE : Plug wit		1 W 05 S B			SCALE NA	-{	ral linear rances: ±	NPRDS / PROJECT <b>859</b>	
<u> </u>	CONTACT TYPE : Standard Crimp Contact   SHELL SIZE : 11 ORIENTATION : B   CONTACT TYPE : SOCKET(500 Matings)					- SOURIAU WWW.SOURIAU.COM SOURI/ it must not be re		This document is the property of SOURIAU it must not be reproduced or		
					-		communicated without permission			
PI	PLATING : W =	Olive drab Cadmium		CONTACT LA	YOUT : 11-05	FORMAT A3		JRIAU DRG N°		HEET
	Н	G	F	E	1			511W05SB-C	A	1/2

	т	G	וד	m		0	
		Contact Layout					
4	-X	$ \begin{array}{c} & & \\ & & \\ & \\ & \\ & \\ & \\ & \\ & \\ & $					
	Shell Arrangement Numb size no.	X-axis (mm)   Y-axis (mm)     +065 (1.65)   +.056 (1.42)     +.113 (2.87)  065 (1.65)     +.000 (0.00)  130 (3.30)    113 (2.87)  065 (1.65)    065 (1.65)   +.056 (1.42)    065 (1.65)  065 (1.65)    065 (1.65)  065 (1.62)    065 (1.65)  065 (1.62)    065 (1.65)  065 (1.62)					
ω							
	$\vdash$					SOURIAU shall not be liab due to a use of the Pro	
N						the Specifications issued by (professional reco	y either c
					A 17-10-20	PN: 8D	0511\
					ISS DATE Designed By: TITLE	Date:	Alumir
-					SCALE NA	Gener	ral linear rances:
					SOURIA		
		1	1		FORMAT A3		IRIAL
	Н	G	F	E	D	C	

