I	G	г	т	D		0		σ	A		_
	Z	ØS-									4
ယ			LAYOUT SHOWN AS EXAMPLE						3		
		Keying Shown as e	example								
	on MIL-DTL-38999 Series III	E	Connector dimensionDimNominalØS48 Max	F							
-Shell Material -Shell Plating -Insulator -Contacts	: Aluminium : Black Zinc Nickel : Thermoplastic : Copper Alloy		ØS48 MaxZ31 MaxVV THREADM37x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)						
-Seals & Gromme -Contact Plating	t : Silicon Elastomer : Gold over copper Alloy 0.8μm mini	imum		L			Country FR		n & Control List t Listed		2
-Durability -Delivered with So	-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories-Temperature Range: -65°C to +175°C-Salt Spray: 500 hours						PN: 8D525Z07BC				
							A 17-10-2016 First Release				
	: 90.7 g ± 10%			ISS Desig	DATE gned By:	Latest modificatio	on - by	CU	STOMER DRAWING	MOD N°	
							Aluminium Plug 8D series				
BASIC SERIES:	8D 5 - 25 g with RFI Shielding	5 Z 07 B C			CALE		General linear Tolerances: ±		NPRDS / PROJECT 859		1
CONTACT TYPE	CONTACT TYPE : Standard Crimp Contact ORIENTATION : C					SOURIAU This document is the property of SOURIAU It must not be reproduced or it					
SHELL SIZE : 25 PLATING : Z	= Black Zinc Nickel		CONTACT TYPE : SOCKET(500 N CONTACT LAYOUT	T : 25-07			SOURIAU	DRG N°	communicated without per	SHEET	
Н	G	F	E	<i>F</i>	43	С	8D525Z0	B	A	1/2	

Г	D I	П	т		0	Φ	A		
	Contact Layout								
4	(Inactive for new design for MIL-DTL-38999. For new design, use arrangement no. 25-9.)								4
	Contacts (Insert arrangement 25-7) Contact position ID Location X-axis ID X-axis (mm) Contact position ID Location 1 494 (12.55) +.242 (6.15) 51 +.000 (0.00) 106 (2.69) 2 533 (13.54) ·.130 (3.51) 52 ·.000 (0.00) 212 (5.30)							-	
ω	4 544 (13.82) 083 (2.11) 54 +.000 (0.00) 551 (14.00) 5 516 (13.11) 191 (4.85) 55 +.056 (1.42) +.548 (13.92) 6 467 (11.86) 292 (7.42) 56 +.095 (2.41) +.461 (11.71) 7 435 (11.05) +.337 (8.56) 57 +.068 (1.73) +.370 (9.40) 8 399 (10.13) +.249 (6.32) 58 +.092 (2.34) +.278 (7.06) 9 441 (11.20) +.163 (4.14) 59 +.095 (2.41) +.183 (4.65) 10 465 (11.81) +.071 (1.80) 60 +.089 (2.26) 178 (4.52) 11 470 (11.94) 024 (0.61) 61 +.094 (2.39) 277 (7.04) 12 456 (11.89) 118 (3.00) 62 +.069 (1.75) 376 (9.55) 13 423 (10.74) 207 (5.26) 63 +.048 (1.22) 468 (11.89) 14 372 (9.45) 288 (7.32) 64 +.165 (4.19) +.525 (13.34)								3
	$ \begin{array}{ c c c c c c c } \hline \begin{tabular}{ c c c c c c } \hline \begin{tabular}{ c c c c c c c } \hline \begin{tabular}{ c c c c c c c } \hline & Location & Location & Location & X-axis & Y-axis & mm & $					le for any non-conformity or ducts which does not comply	_		
2	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$				(professional recor PN: 80				2
	42 089 (2.26) 178 (4.52) 92 +.372 (9.45) 288 (7.32) Contacts (Insert arrangement 25-7) Contact position ID Location Location Variable (mm) Contact (mm) Contact position ID Y-axis (mm) Y-axis (mm)			A 17-10-2016 ISS DATE Designed By:	First Release Latest modification - by Date:	CL	JSTOMER DRAWING	MOD N°	—
	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$			TITLE		Aluminium Plug 8D s			
-	50 +.000 (0.00) +.000 (0.00) Shell size ment no. Arrange- of contacts Number of contacts Size contacts Service contacts Contact Pin Socket 25 7 2 8 (See note) Twinax 25, 75 M39029/90-529 M39029/91-530 97 22D M All others M39029/56-348 M39029/56-348					ances: 	NPRDS / PROJECT 859 This document is the property SOURIAU		1
			1	FORMAT A3	SOU	RIAU DRG N° 525Z07BC-C	it must not be reproduced of communicated without permis		
L	H G	F	E	D	C	В	A		