


OM3 can support 40GBASE-SR4 / 100GBASE-SR10 in applicable parallel optics networks

10Gb Duplex Multimode 50/125 OM3 LSZH Fiber Patch Cable (LC/SC) - Aqua, 3M (10 ft.)

MODEL NUMBER: N816-03M



Highlights

- Designed for 10-Gig Ethernet applications...OM3 Rated
- Backward compatible with existing 50/125 fiber
- Max 10Gb distance of 300 meters @850nm
- Low-Smoke, Zero Halogen (LSZH) Aqua jacket

Package Includes

• 3 meter Duplex Multimode 50/125 Aqua OM3 Fiber Patch Cable, SC/LC

Features

- 10gb Ethernet speed to 300 meters @850nm, OM3 rated
- Use with VCSEL and LED laser light sources
- High-Speed, High-Bandwidth, Low-Cost
- Backward compatible with legacy LAN's
- Ideal for Fibre Channel (SAN) applications
- IEEE 802.3ae and TIA LOMMF compliant

Specifications

| OVERVIEW | | |
|-------------------------|--------------|--|
| UPC Code | 037332124838 | |
| Technology | Multimode | |
| Optical Mode | OM3 | |
| PHYSICAL | | |
| Cable Jacket Color | Aqua | |
| Connector Color | White; Beige | |
| Cable Jacket Material | LSZH | |
| Cable Jacket Rating | OFNR | |
| Clad Diameter (microns) | 125 | |



| Core Diameter (microns) | 50 | |
|---------------------------------|---|--|
| Number of Fibers | 2 | |
| Cable Length (ft.) | 9.8 | |
| Cable Length (m) | 2.99 | |
| Cable Length (in.) | 118.1 | |
| Minimum Bend Radius | 20 mm (Dynamic); 10 mm (Static) | |
| Shipping Dimensions (hwd / in.) | 0.25 x 6.00 x 8.00 | |
| Shipping Dimensions (hwd / cm) | 0.64 x 15.24 x 20.32 | |
| Shipping Weight (lbs.) | 0.10 | |
| Shipping Weight (kg) | 0.05 | |
| Fiber Cable Length | 3M (9.8 ft) | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | -4° to 140°F (-20° to 60°C) | |
| Storage Temperature Range | -4° to 140°F (-20° to 60°C) | |
| Operating Humidity Range | 5% to 85% RH, Non-Condensing | |
| Storage Humidity Range | 35% to 65% RH, Non-Condensing | |
| Corago Harmany Hange | construction containing | |
| COMMUNICATIONS | | |
| Network Compatibility | 1 Gbps (Gigabit); 10 Gbps; 25 Gbps; 40 Gbps; 100 Gbps | |
| Attenuation @ 850NM | 3.0 dB/km | |
| Insertion Loss | LC 0.20 dB; SC 0.20 dB | |
| CONNECTIONS | | |
| Side A - Connector 1 | SC DUPLEX (MALE) | |
| Side B - Connector 1 | LC DUPLEX (MALE) | |
| Endface Polish | PC | |
| FEATURES & SPECIFICATIONS | | |
| Push/Pull Tabs | No | |
| Breakout | No | |
| Trunk | No | |
| STANDARDS & COMPLIANCE | | |
| Product Compliance | RoHS; REACH | |
| WARRANTY & SUPPORT | | |



| Product Warranty Period (Worldwide) | Lifetime limited warranty |
|-------------------------------------|---------------------------|
|-------------------------------------|---------------------------|



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.