



注) NOTES:

1. 材質 MATERIAL  
黄銅 (板厚: 0.3)  
BRASS (THICKNESS: 0.3)
2. メッキ仕様 TERMINAL PLATING  
接点部 : 金メッキ 0.1μm MIN.  
CONTACT AREA : GOLD 0.1 MICROMETER MINIMUM.  
 : パラジウムニッケルメッキ 0.6μm MIN.  
 : PD-NI 0.6 MICROMETER MINIMUM.  
圧着部 : 錫メッキ 1.0 μm MIN.  
CRIMP AREA : TIN 1.0 MICROMETER MINIMUM.  
下地メッキ : ニッケルメッキ 1.5 μm MIN.  
UNDER PLATE : NICKEL 1.5 MICROMETER MINIMUM.
3. 適用電線範囲: UL 1015, UL 1865, AWG #16~14  
APPLICABLE WIRE RANGE: UL 1015, UL 1865, AWG #16~14
4. 被覆外径 : φ3.8 MAX.  
INSULATION EXTERNAL DIA: φ3.8 MAX.
5. 50638-9028 は 50638-9049 の鉛フリー品である。  
50638-9128 は 50638-9149 の鉛フリー品である。  
50638-9028 IS LEAD FREE OF 50638-9049.  
50638-9128 IS LEAD FREE OF 50638-9149.

DO NOT SCALE DRAWING

64 NO. DRWN: CH'K: APPR:	63 NO. DRWN: CH'K: APPR:	62 NO. DRWN: CH'K: APPR:	61 NO. DRWN: CH'K: APPR:	新規作成 RELEASED 60 NO. J2004-4129 DRWN: M.NAGATA '04/05/10 CH'K: K.TOJO '04/05/10 APPR: M.SASAO '04/05/10
-----------------------------	-----------------------------	-----------------------------	-----------------------------	---

MATERIAL 材料	— # —
FINISH 仕上げ	— # —
WIRE RANGE 適用電線範囲	— # —
INS. RANGE 被覆外径	— # —

GENERAL TOLERANCES: (UNLESS SPECIFIED) 一般公差	10 UNDER 未満 ±0.2	10 OVER 30 UNDER 未満 ±0.25	30 OVER 以上 ±0.3
ANGLE 角度	±3°		

MODEL NO. 50638-****	DIMENSIONS: <input type="checkbox"/> mm <input type="checkbox"/> INCH <input checked="" type="checkbox"/> mm ONLY		SHT	REV
SCALE 5:1	DESIGN UNITS <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH	TITLE: 2mm PITCH AC/DC CONN. PLUG CRIMP TERM. (M II DRAWER CONNECTOR) -LEAD FREE-		
DRAWN BY & DATE M.NAGATA '04/05/10		APPROVED BY & DATE M.SASAO '04/05/10		
CHECKED BY & DATE K.TOJO '04/05/10		MATERIAL NO. SEE CHART		
DRAWN BY & DATE M.SASAO '04/05/10		DRAWING NO. SD-50638-001		
CAD FILENAME SD-50638-001.S01		SHEET NO. 1 OF 1		

バラ状 LOOSE	50638-9128
連鎖状 CHAIN	50638-9028
端子形状 TERMINAL CONFIGURATION	MATERIAL NO.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION. SIZE B