<u>Contact Dimensions:</u>
525-P.C. Tail .018 Sq.(0.46 Sq.) - Tail LG=.150(3.81)
.100 (2.54) Contact Spacing x .200 (5.08) Row Spacing 1 -2x Ø.156[3.96] CARD SLOT ACCEPTS .054" [1.37] TO .070"[1.78] THICK PCB 6.300 160.02 6.460 164.08 -6.775 172.09 .160[4.06] POINT OF CONTACT CARD SLOT 330 [8.38] EDRG **SECTION A-A** 600 [15.24] 250 [6.35] -7.035 [178.69]

INSULATOR MATERIAL: THERMOPLASTIC PBT BLACK, UL 94V-0

CONTACT MATERIAL; COPPER TIN ALLOY CONTACT PLATING: GOLD ON THE MATING AREA, TIN PLATING ON THE CONTACT TAILS, NICKEL UNDERPLATE

| 345/395 SERIES CARD EDGE CONNECTO | R |
|-----------------------------------|---|
| PART NUMBER: 395-062-525-488 | |

YOUR CONNECTION TO QUALITY & SERVICE

| ACAD REFERENCE NO | . 345-ENG | G-MASTER |
|---------------------|-----------|-----------|
| DRAWN: R.STA.MONICA | DATE:MA | Y.16/2017 |
| CHECKED: | DATE: | |
| SCALE: 1:1 | SHEET ' | OF 2 |
| DRAWING NUMBER | | ISSUE |
| 345-ENG-MASTER | | 1 |



.107 [2.72] .082 [2.08] .157 [4] .232 [5.89] .125(3.18) to .210(5.33) .125(3.18) to .210(5.33) Outside Tails Outside Tails .045(1.14) to .060(1.52) .045(1.14) to .060(1.52) Between Tails Between Tails **Contact Code 555 Contact Code 556**







Contact Code 558

Contact Code 559

Contact Code 560

INSULATOR MATERIAL: THERMOPLASTIC POLYESTER, UL 94V-0

DAP MATERIAL AVAILABLE UPON REQUEST

CONTACT MATERIAL; COPPER ALLOY

CONTACT PLATING: GOLD ON THE MATING AREA, TIN PLATING ON THE CONTACT TAILS, NICKEL UNDERPLATE

345/395 SERIES CARD EDGE CONNECTOR CONTACT CODE 555,556,558,559,560 DIMENSIONS

YOUR CONNECTION TO QUALITY & SERVICE

| | ACAD REFERENCE NO | . 345-ENG-MASTER |
|----|---------------------|------------------|
| 5 | DRAWN: R.STA.MONICA | DATE:MAY.16/2017 |
| | CHECKED: | DATE: |
| , | SCALE: 1:1 | SHEET 2 OF 2 |
| ΞD | DRAWING NUMBER | ISSUE |

345-ENG-MASTER