

## C1812C220JHRACTU

Aliases (C1812C220JHRAC7800)

SMD Comm X7R HV, Ceramic, 22 pF, 5%, 3000 VDC, X7R, SMD, MLCC, High Voltage, Temperature Stable, 1812



Click [here](#) for the 3D model.

### Dimensions

|           |                 |
|-----------|-----------------|
| Chip Size | 1812            |
| L         | 4.5mm +/-0.3mm  |
| W         | 3.2mm +/-0.3mm  |
| T         | 1mm +/-0.10mm   |
| B         | 0.6mm +/-0.35mm |

### Packaging Specifications

|                    |                          |
|--------------------|--------------------------|
| Packaging          | T&R, 180mm, Plastic Tape |
| Packaging Quantity | 1000                     |

### General Information

|                  |   |
|------------------|---|
| Series           | SMD Comm X7R HV                             |
| Style            | SMD Chip                                    |
| Description      | SMD, MLCC, High Voltage, Temperature Stable |
| Features         | High Voltage                                |
| RoHS             | Yes   |
| Termination      | Tin   |
| Marking          | No  |
| AEC-Q200         | No  |
| Component Weight | 95 mg                                       |
| Shelf Life       | 78 Weeks                                    |
| MSL              | 1   |

### Specifications

|  |   |
|--|---|
| Capacitance  | 22 pF   |
| Measurement Condition  | 1 kHz 1.0Vrms                                   |
| Capacitance Tolerance  | 5%  |
| Voltage DC   | 3000 VDC  |
| Dielectric Withstanding Voltage                                    | 3600 VDC  |
| Temperature Range  | -55/+125°C                                      |
| Temperature Coefficient  | X7R   |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC) | 15%, 1kHz 1.0Vrms                               |
| Dissipation Factor   | 2.5% 1kHz 1.0Vrms                               |
| Aging Rate   | 3% Loss/Decade Hour: Referee Time is 1000 Hours |
| Insulation Resistance  | 100 GOhms                                       |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.