

GRM3195C2A153JA01J

Note: This datasheet may be out of date.

Please download the latest datasheet of GRM3195C2A153JA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GRM3195C2A153JA01%23

"#" indicates a package specification code.
















Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
Applications Specific Applications	these "Precautions for use." Consumer equipment,Industrial Equipment,Mobile Electronics,Medical equipment [GHTF A/B/C] except for implant equipment,Automotive infotainment/comfort equipment Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual
	Product.



References

	Specifications	Standard
Packaging		Packing
		Quantity
D	φ180mm Reel Paper Tape	4000
J	φ330mm Reel Paper Tape	10000

Mass (typ.)	
1 piece	19.0mg



Appearance & Shape





1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GRM3195C2A153JA01J

Note: This datasheet may be out of date.

Please download the latest datasheet of GRM3195C2A153JA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GRM3195C2A153JA01%23

"#" indicates a package specification code.



Specifications

Length	3.2±0.15mm	
Width	1.6±0.15mm	
Thickness	0.85±0.1mm	
Capacitance	15000pF ±5%	
Distance between external terminals g	1.5mm min.	
External terminal size e	0.3 to 0.8mm	
Operating Temperature Range	-55°C to 125°C	
Rated Voltage	100Vdc	
Size code in inch(mm)	1206 (3216M)	
тс	0±30ppm/°C	
Temperature characteristics	COC(FIA)	
(complied standard)	C0G(EIA)	
Temperature range of	25°C to 125°C	
temperature characteristics	20 C to 120 C	

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

