



注：
NOTE

1. 材料 MATERIAL
ピン : □0.635×14.2 黄銅、
ニッケル下地金めっき
PIN : □0.635×14.2 BRASS
GOLD OVER NICKEL PLATING
ウエハー : ポリアミド、UL94V-0
WAFER: POLYAMIDE,UL94V-0
2. 6極以上に適応
TO BE APPLIED FOR 6 CKT. AND MORE THAN 6 CKT.
3. 5極以下はロック部スリットなし
NO SLIT IS PROVIDED FOR 5 CKT. AND LESS THAN 5 CKT.
4. ELV 及び RoHS 適合品
ELV AND RoHS COMPLIANT



1.35	0.85	35	+0.3 -0.45	35	22 11 1151	15
↑	↑	32.5	+0.25 -0.45	32.5	↑ 1141	14
		30	+0.25 -0.4	30	↑ 1131	13
		27.5	+0.25 -0.4	27.5	↑ 1121	12
		25	+0.2 -0.4	25	↑ 1111	11
		22.5	+0.2 -0.4	22.5	↑ 1101	10
		20	+0.15 -0.35	20	↑ 1091	9
		17.5	+0.15 -0.35	17.5	↑ 1081	8
		15	+0.1 -0.3	15	↑ 1071	7
		12.5	+0.1 -0.3	12.5	↑ 1061	6
		10	+0.15 -0.3	10	↑ 1051	5
1.35	0.85	7.5	+0.15 -0.3	7.5	↑ 1041	4
1.2	1	5	+0.15 -0.3	5	↑ 1031	3
1.2	1	2.5	+0.15 -0.3	2.5	↑ 22 11 1021	2
D	C	B	A	ORDER No.	極数	CKT.

MODEL No. : 5045-**AG

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

EC NO: 168849 DRWN: QHE31 CHK'D: SAKIYAMA APPR: TKANEKO	2017/11/28	2017/11/30	2017/12/26	GENERAL TOLERANCES (UNLESS SPECIFIED) ANGULAR TOL ± 3.0 ° 4 PLACES ± 0.2 3 PLACES ± 0.2 2 PLACES ± 0.2 1 PLACE ± 0.2 0 PLACES ± 0.2 DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DIMENSION UNITS	SCALE		
	REVISED	mm	5:1					
	DRWN BY	DATE	RHORI		2013/11/25			
	CHK'D BY	DATE	KASAKAWA		2013/11/28			
	APPR BY	DATE	NUKITA		2013/11/28			
DRAWING SIZE		THIRD ANGLE PROJECTION		PRODUCT CUSTOMER DRAWING		SERIES	MATERIAL NUMBER	CUSTOMER
A3				5045		SEE CHART	GENERAL MARKET	
G		REV		DOCUMENT NUMBER		DOC TYPE	DOC PART	SHEET NUMBER
				SD-5045-001		PSD	001	1 OF 1