	T	Q	П	т		0
4 3	R 22.6 Max					LA
			Keying Shown as	example		
N	-Durability : 500 Mating	eel tic γ omer opper Alloy 0.8μm minimum cycles		Connector dimension           Dim         Nominal           A         38.1±0.3           B         23.82+0.1/-0.15           R         32.5Max           S         34.9±0.4           W         2.2+0.9/-0.1           VV THREAD         M18x1-6g		SOURIAU shall due to a use the Specification (profess
	-Delivered with Souriau contacts and -Temperature Range <u>:</u> -65°C to +20 -Salt Spray : 500 hours				ISS DAT Designed By:	2016 First Release E Latest modificat Dates
<b>_</b>	SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Co	8D 7 - 13 S	5 04 P B		TITLE SCALE NA NTATION : B SOURIA	
	SHELL SIZE : 13 PLATING : S = Nickel			CONTACT TYPE : PIN(5 CONTACT LAY		
			1		A3	
	Н	G	F	E	D	С

D	A					
		4				
LAYOUT SHOWN AS EXAMPLE						
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) <u>Country</u> Jurisdiction & Control List FR Not Listed PN: 8D713S04PB						
ation - by MOD N° te: CUSTOMER DRAWING Stainless Steel Receptacle 8D series						
General linear Tolerances: ±	NPRDS / PROJECT 859 This document is the pro SOURIAU	perty of				
W.SOURIAU.COM SOURIAU DRG M 8D713S04PB-0	C					
I B	I A					

Г	T G	П	m	
4	$\begin{array}{c} & \overbrace{x_{1}}^{\bullet} \stackrel{Y}{\bigoplus} $			Panel cutout JAM NUT RECEPTACLE (TYPE 7)
	Contact position ID         X-axis (mm)         Y-axis (mm)           A         +.000 (0.00)         +.150 (3.81)           B         +.146 (3.71)         +.035 (0.89)           C         +.000 (0.00)        083 (2.11)           D        146 (3.71)         +.035 (0.89)           Shell         Arrangement no.         Number of contacts         Size contacts         Service rating         Contact location           13         -4         4         16         I         All	Supersedes MS20051-4		
ω				Dim         Nominal           B         24.26+0/-0.25           ØC         25.65+0.25/-0
				SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)
2				Country       Jurisdiction & Control List       2         FR       Not Listed       2         PN: 8D713S04PB
				A     28-09-2016     First Release       ISS     DATE     Latest modification - by       Designed By:     Date:     CUSTOMER DRAWING
				TITLE     Stainless Steel Receptacle 8D series
<u> </u>				SCALE     General linear     NPRDS / PROJECT       NA     Image: Description of the second
				SOURIAU       This document is the property of SOURIAU         SOURIAU       it must not be reproduced or communicated without permission
				FORMATSOURIAU DRG N°SHEETA38D713S04PB-C2/2
L	H G	F	E	D C B A