

ATGBICS FCLF8522P2BTL-C network transceiver module Copper 1250 Mbit/s RJ-45

Brand : ATGBICS

Product code: FCLF8522P2BTL-C

Product name : FCLF8522P2BTL-C



FCLF8522P2BTL ATGBICS Finisar Compatible Transceiver SFP 10/100/1000Base-T Copper RJ45 Connector 100m

ATGBICS FCLF8522P2BTL-C network transceiver module Copper 1250 Mbit/s RJ-45:

FCLF8522P2BTL 1000BASE-T SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. Finisar 1000BASE-T SFP modules support 10/100/1000 auto negotiation and auto MDI/MDIX. Our product is built to the exact specification of Finisar FCLF8522P2BTL= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

ATGBICS FCLF8522P2BTL-C. SFP transceiver type: Copper, Maximum data transfer rate: 1250 Mbit/s, Interface type: RJ-45. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 4 V, Power consumption (typical): 1.3 W. Width: 13.4 mm, Depth: 56.6 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box



Performance		Features	
SFP transceiver type *	Copper	Country of origin	United Kingdom
Maximum data transfer rate *	1250 Mbit/s	Brand compatibility	Finisar
Interface type *	RJ-45	Power	
Single-mode fiber (SMF) supported	✗	Input voltage	3.3 V
Multi-mode fiber (MMF) supported	✗	Maximum voltage	4 V
Fiber optic connector	SFP	Power consumption (typical)	1.3 W
SFP transceiver standard	TX	Operational conditions	
Maximum transfer distance	100 m	Maximum operating temperature	70 °C
Ethernet LAN	✓	Operating temperature (T-T)	0 - 70 °C
Ethernet interface type	Gigabit Ethernet	Storage temperature (T-T)	-40 - 85 °C
Networking standards	IEEE 802.3	Operating relative humidity (H-H)	5 - 85%
Copper ethernet cabling technology	10BASE-T,100BASE-TX,1000BASE-TX	Storage relative humidity (H-H)	5 - 85%
Auto MDI/MDI-X	✓	Weight & dimensions	
Digital Diagnostics Monitoring (DDM)	✗	Width	13.4 mm
Features		Depth	56.6 mm
Product colour	Silver	Height	8.5 mm
Housing material	Metal	Weight	24 g
Plug and Play	✓	Packaging data	
Hot-Plug support	✓	Number of products included	1 pc(s)
Hot-swap	✓	Package type	Box
Easy to install	✓	Technical details	
		Sustainability certificates	RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.