



.XX ±0.13 .XXX ±0.05



ISSUE NUMBER	
ORIGINAL	1





NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED

POWER/CO-AX CONTACT RATING:	50Ω (IMPEDANCE)
(IF PRESENT) SIGNAL CONTACT CURRENT RATING:	
SIGNAL CONTACT CORRENT RATING.	$10m\Omega$ MAX.
	E000MO min


INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

OPERATING TEMPERATURE:


5000MΩ min.


-55°C ~ 125°C

1000V AC rms



	COMBINATION D-SUB		SW REFERENCE NO.: 629 COMBO ASSEMBLY		
			DRAWN: C.B	DATE: JAN. 01/20	19
			CHECKED:	DATE:	
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
		SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS	DRAWING NUMBER: 629-13W	3240-5NE	ISSUE
YOUR CONNECTION TO	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 629-13W	3240-5NE	1





COMPLIANT

