TOLERANCE
 THIS IS A C.A.D. GENERATED DRAWING


 UNLESS OTHERWISE SPECIFIED
 DO NOT MAKE MANUAL REVISIONS TO MASTER.


 .X
 ±0.25



ISSUE NUMBER	
ORIGINAL	

(1)





6.10

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

(IF PRESENT)

OPERATING TEMPERATURE:

.XX ±0.13 .XXX ±0.05

POWER/CO-AX CONTACT RATING: 50Ω (IMPEDANCE

SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 50Ω (IMPEDANCE) G: 5A PER CONTACT 10mΩ MAX.

-55°C ~ 125°C

STEEL, NICKEL PLATED

 $5000M\Omega$ min.



	SW REFERENCE NO.: 629 COMBO ASSEMBLY			
		DRAWN: C.B	DATE: JAN. 01/20	19
		CHECKED:	DATE:	
EDAC INC	ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
TORONTO, ONTARIO CANADA		DRAWING NUMBER: 629-3WK	3240-5N4	ISSUE
YOUR CONNECTION TO QUALITY & SERVICE	MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBER: 629-3WK	3240-5N4	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY. 1000V AC rms

THERMOPLASTIC POLYESTER, UL94V-0

COPPER ALLOY, GOLD FLASH PLATED

