Ξ	٦	m		D		0	₽		Þ	
	M Thread									4
ω	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~					LAYOUT SHOWN A	S EXAMPLE			3
CHARACTERISTICS	Keying Sh	hown as example								
-Standard : Based on MIL-DTL-38999 Series III		Connector dimension Dim Nomina	1							
-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy	0.8μm minimum	ØS 29.4 Ma Z 31 Max VV THREAD M18x1-6				SOURIAU shall not be liable for due to a use of the Products the Specifications issued by eithe (professional recommen	which does not cor r of the Parties or b dation, technical no	nply with y a third party		2
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories										
-Temperature Range <u>-</u> -65°C to +175°C				A 1	.8-10-2016	First Release				
-Salt Spray : 500 hours				ISS	DATE	Latest modification - by			MOD N°	•
				Designed	By:	Date:		CUSTOMER DRAWI	NG	
			TITLE		ITLE	Aluminium Plug 8D series				
BASIC SERIES: 8D 5 SHELL TYPE : Plug with RFI Shielding	- 13 W 03 A	c		SCALE	-	General linea Tolerances:		NPRDS / PROJECT 859	-	_
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13		CONTACT TYPE : I	ORIENTATION : C PIN(500 Matings)	SOU	IRIAU	WWW.SOURIAU	.COM	This document is th SOURI/ it must not be re communicated with	AU produced or	
PLATING : W = Olive drab Cadmium			LAYOUT : 13-03	FORMA	т	SOURIA	U DRG N°		SHEET	\neg
	I			A3			W03AC-C		1/2	
H G	F	E		D		C	В		Α	

	т	۵	н т	п		C	
		Contact Layout					
4		3#16					
	Ctc A B C	13-03 X Y 2.39 1.47 0 -2.79 -2.39 1.47					
ω							
	_						
						SOURIAU shall not be due to a use of the the Specifications issue (professional re	e Products v d by either
N							Coun FR
						PN: 8	8D513
					A 18-10-2016	First Release	
					ISS DATE Designed By:	Latest modification - by Date:	
					TITLE		Alumi
_					SCALE NA		eneral linear olerances: ±
					SOURIAU	WWW.SOU	JRIAU.
					FORMAT	SC	URIA

G

Н

F

Е

A3

D

С

