

Product: <u>1326A</u> ☑

Security & Sound, 3 Pair 22 AWG BC, Individually Shielded, CMP



Product Description

Security & Commercial Audio Cable, 3 Pair 22 AWG stranded bare copper pairs with Flamarrest® insulation, individually Beldfoil® shields, Plenum-CMP, Flamarrest® jacket

Technical Specifications

Product Overview

Suitable Applications:	Sound and Audio Systems, Intercom and PA Systems, Security Systems, Access Control Systems, Power-Limited Control Systems

Construction Details

Conductor

Element	Number of Element	Size	Stranding	Material
Pair(s)	3	22 AWG	7x30	TC - Tinned Copper

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Pair(s)	PVC - Polyvinyl Chloride	0.0095 in (0.24 mm)	0.048 in (1.2 mm)	Black & Red, Black & Green, Black & White

Inner Shield

Shield Type Material		Coverage	Drainwire Type
Таре	Bi-Laminate (Alum+Poly)	100%	24 AWG (7x32) TC

Outer Shield

Material No Shield

Outer Jacket

	Material	Nom. Thickness	Nom. Diameter
PVC	- Polyvinyl Chloride	0.014 in (0.36 mm)	0.19 in
Ove	rall Cable Diameter (I	Nominal): 0.19 in	

Electrical Characteristics

Electricals

Nom. Conductor DCR	Nom. Inner Shield DCR	Nom. Capacitance Cond-to-Cond	Max. Current
18.2 Ohm/1000ft	8.6 Ohm/1000ft (28 Ohm/km)	34 pF/ft (110 pF/m)	4.2 Amps per Conductor at 30°C

Voltage

UL Voltage Rating 300 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	0°C to +75°C

Bend Radius

Stationary Min.	Installation Min.
1.9 in (48 mm)	1.9 in
Max. Pull Tension	n:
Bulk Cable Weigh	ht:

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262 (UL 910), FT6, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	8777

History

Update and Revision:	Revision Number: 0.389 Revision Date: 12-20-2022

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
1326A D15500	Blue	Reel	500 ft	612825111979
1326A D151000	Blue	Reel	1,000 ft	612825111962
1326A 009500	White	Reel	500 ft	612825111993
1326A 0091000	White	Reel	1,000 ft	612825111986
1326A 009Z1000	White	ReelTuff Box	1,000 ft	612825426615

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.