

Product data sheet

Characteristics

NSYTBP191610H
PC box IP66 IK08 RAL7035
Int.H175W150D100 Ext.H193W164D105
opaque PC cover H40



Main

| | |
|---------------------|--|
| Range | Thalassa |
| Product name | Thalassa TBP |
| Device Application | Multi-purpose |
| Category | Industrial box |
| Height | 7.56 in (192 mm) |
| Width | 6.46 in (164 mm) |
| Depth | 4.13 in (105 mm) |
| Internal height | 6.89 in (175 mm) |
| Internal width | 5.91 in (150 mm) |
| Internal depth | 3.94 in (100 mm) |
| Enclosure mounting | Wall mounted |
| Device composition | 1 body 1 cover 4 cover screw |
| Body type | One piece moulded |
| Type of front cover | High plain cover |
| Cover fixing | Plastic screws |
| Lock type | Captive screw flat outside sealed area |
| Removable parts | Cover by captive screws |

Complementary

| | |
|-----------------------------|-----------------------|
| Material | polycarbonate |
| Color | Gray RAL 7035) |
| Standards | UL 508 A IEC 62208 |
| Product Certifications | TÜV UL |
| Electrical Insulation Class | Class II |
| Mounting location | Outdoor |
| Net Weight | 1.37 lb(US) (0.62 kg) |

Environment

| | |
|-------------------------------------|------------------------------|
| IP degree of protection | IP66 conforming to NEMA 4.4X |
| IK degree of protection | IK08 IEC 62262 |
| Fire resistance | 1760 °F (960 °C) |
| Ambient Air Temperature for Storage | 5...140 °F (-15...60 °C) |
| Operating temperature | -13...176 °F (-25...80 °C) |

Ordering and shipping details

| | |
|-----------------------|-----------------------------------|
| Category | 80033-ENCLOSURE SYSTEMS POLYESTER |
| Discount Schedule | ES1 |
| GTIN | 3606480165672 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 21.06 oz (597.0 g) |
| Returnability | Yes |
| Country of origin | HU |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 4.72 in (12.0 cm) |
| Package 1 width | 6.69 in (17.0 cm) |
| Package 1 Length | 8.07 in (20.5 cm) |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 17 |
| Package 2 Weight | 24.12 lb(US) (10.94 kg) |
| Package 2 Height | 15.75 in (40.0 cm) |
| Package 2 width | 16.14 in (41.0 cm) |
| Package 2 Length | 24.02 in (61.0 cm) |
| Unit Type of Package 3 | PAM |
| Number of Units in Package 3 | 425 |
| Package 3 Weight | 632.73 lb(US) (287.0 kg) |
| Package 3 Height | 84.65 in (215.0 cm) |
| Package 3 width | 39.37 in (100.0 cm) |
| Package 3 Length | 47.24 in (120.0 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|