


T368D107M020AT7303

T368, Tantalum, MnO2 Tantalum, Commercial Grade, 100 uF, 20%, 20 VDC, Radial, Solid Tantalum, Conformal, Retangular Anode, Lead Spacing = 6.35mm



General Information Series T368 Dielectric MnO2 Tantalum Style Radial Description Radial, Solid Tantalum, Conformal, Retangular Anode Features **Rectangular Anode** RoHS Yes Termination Tin AEC-Q200 No Notes Longest Lead Is Positive.

Specifications	
Capacitance	100 uF
Capacitance Tolerance	20%
Voltage DC	20 VDC (85C), 1 VDC (85C Reverse)
Temperature Range	-55/+85°C
Dissipation Factor	8%
Leakage Current	10 uA

Click here for the 3D model.

Dimensions	,
W	11.68mm
н	13.2mm +2.54mm
т	6.35mm
S	6.35mm +/-0.38mm
LL	4.75mm +/-0.81mm
НО	18mm MIN
F	0.64mm +/-0.05mm

Packaging Specifications	
Packaging	T&R, 305mm
Packaging Quantity	500

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.