



Contact Layout



(Inactive for new design for MIL-DTL-38999. For new design, use arrangement no. 19-19.)

| Contacts<br>(Insert arrangement 19-18) |             |             |                     |             |             |                  |
|--|-------------|-------------|---------------------|-------------|-------------|------------------|
| Contact position ID                    | Location    |             | Contact position ID | Location    |             | Standard contact |
|  | X-axis (mm) | Y-axis (mm) |                     | X-axis (mm) | Y-axis (mm) |                  |
| A                                      | +068 (1.73) | +380 (9.65) | K                   | -180 (4.57) | -180 (4.57) | M39029/90-529    |
| B                                      | +180 (4.57) | +180 (4.57) | L                   | -377 (9.58) | -065 (1.65) |                  |
| C                                      | +377 (9.58) | +065 (1.65) | M                   | -317 (8.05) | +000 (0.00) | M39029/58        |
| D                                      | +317 (8.05) | +000 (0.00) | N                   | -377 (9.58) | +065 (1.65) |                  |
| E                                      | +377 (9.58) | -065 (1.65) | P                   | -180 (4.57) | +180 (4.57) | M39029/91-530    |
| F                                      | +180 (4.57) | -180 (4.57) | R                   | -068 (1.73) | +380 (9.65) |                  |
| G                                      | +068 (1.73) | -380 (9.65) | S                   | +000 (0.00) | +319 (8.10) | M39029/56        |
| H                                      | +000 (0.00) | -319 (8.10) | T                   | +000 (0.00) | +044 (1.12) |                  |
| J                                      | -068 (1.73) | -380 (9.65) | U                   | +000 (0.00) | -044 (1.12) |                  |

  

| Shell size | Arrangement No. | Number of contacts | Size contacts (see note) | Service rating | Contact location | Standard contact |               |
|------------|-----------------|--------------------|--------------------------|----------------|------------------|------------------|---------------|
|            |                 |                    |                          |                |                  | Pin              | Socket        |
| 19         | 18              | 4                  | 8                        | Twinax         | B, F, K, P       | M39029/90-529    | M39029/91-530 |
|            |                 | 14                 | 22D                      | M              | All others       | M39029/58        | M39029/56     |

Panel Cutout



| Dim | Nominal    |
|-----|------------|
| ØA  | 32.96 min  |
| ØAA | 28.98 min  |
| R1  | 29.36      |
| ØT  | 3.25 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

**PN: 8D019S18BA**

|                |   |                                |   |
|----------------|---|--------------------------------|---|
| A              | 08-10-2016                                  | First Release                  |   |
| ISS            | DATE  | Latest modification - by       | MOD N°  |
| Designed By:   |   | Date:                          | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Stainless Steel Receptacle 8D series</b> |                                |   |
| SCALE          |   | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>   |
| NA             |   |                                |   |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                      |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D019S18BA-C</b>          |                                | SHEET<br>2/2  |