<u>م</u> ا	г	m	D		0	D			٦
	N Thread								-
					LAYOUT SHO	OWN AS EXAMPLE			
	Keying Sh	own as example							
CHARACTERISTICS		Connector dimension]						
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite		Dim Nominal ØS 25 Max							-
-Shell Material : Composite -Shell Plating : Without Plating		Z 31 Max VV THREAD M15x1-6g]			ble for any non-conformity c oducts which does not comp			
-Insulator : Thermoplastic		VV HINLAD MITOXI-OB			the Specifications issued b	y either of the Parties or by a	a third party		
-Contacts : Copper Alloy					(professional reco	mmendation, technical notion	ce.)		
-Seals & Grommet : Silicon Elastomer						Country	ion & Control List]	
-Contact Plating : Gold over copper Alloy 0.8μm r	ninimum			CountryJurisdiction & Control ListFRNot Listed					
-Durability : 500 Mating cycles									
-Delivered with Souriau contacts and Accessories				PN: 8D511X01PD					
-Temperature Range : -65°C to +175°C				10 10 2010	First Dalages			1	
-Salt Spray : 2000 hours			A	18-10-2016	First Release				Ĩ
Mass : 12.8 g ± 10%			ISS		Latest modification - by			MOD N°	_
			Design	ied By:	Date:		CUSTOMER DRAWING		_
				TITLEComposite Plug 8D series			series		
BASIC SERIES: 8D 5 -	11 X 01 P		SCA	ALE		ral linear	NPRDS / PROJECT		
SHELL TYPE : Plug with RFI Shielding			N	IA -t:		rances: ±	859		
							This document is the prop	perty of	_
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11		CONTACT TYPE : PIN(URIAU	WWW.SOUF	RIAU.COM	SOURIAU it must not be reproduc		
				MAT			communicated without per		
		CONTACTIA	YOUT:11-01 FORI	IVIAI	SOL	IRIAU DRG N°		SHEET	Ĩ
PLATING : X = Without Plating		connerex	A	2		511X01PD-C		1/2	

r	т	۵	г – – –	m		0	
		Contact Layout					
4		01					
		1 # 12 11-01	7				
ى	Ctc A	X Y 0 0					
	I						
	F					SOURIAU shall not be liable t due to a use of the Produ the Specifications issued by eit (professional recomm	icts wh ther of
N						PN: 8D5	Countr FR
					ISS DATE	6 First Release Latest modification - by	
					Designed By: TITLE SCALE		mpo
_					SOURIAL	General lin Toleranc ±	ces:
					FORMAT A3	SOURI 8D51	IAU
L	Н	G	F	E	D	C	

