



Click [here](#) for the 3D model.

### Dimensions

|    |                 |
|----|-----------------|
| L  | 41mm -0.7mm     |
| H  | 28.5mm -0.7mm   |
| T  | 16mm -0.7mm     |
| S  | 37.5mm +/-0.5mm |
| LL | 4mm +2mm        |
| F  | 1mm +/-0.05mm   |
| G  | 0.5mm NOM       |

### Packaging Specifications

|                    |            |
|--------------------|------------|
| Packaging          | Pizza, Box |
| Packaging Quantity | 140        |

### General Information

|                  |   |
|------------------|---|
| Series           | F463  |
| Dielectric       | Metallized Polypropylene  |
| Style            | Radial  |
| Features         | MKP, Pulse  |
| RoHS             | Yes   |
| Lead             | Cut/Short   |
| AEC-Q200         | No  |
| Component Weight | 23 g  |
| Miscellaneous    | The Rated Voltage Decreases 2%/C Between +85C And +105C (1.25%/C For AC). ClimCat: 55/105/56. |
| Notes            | Series Replaced by R75.   |

### Specifications

|                       |                           |
|-----------------------|---------------------------|
| Capacitance           | 0.22 uF                   |
| Capacitance Tolerance | 10%                       |
| Voltage AC            | 700 VAC                   |
| Voltage DC            | 2000 VDC, 1200 VDC (105C) |
| Temperature Range     | -55/+105°C                |
| Rated Temperature     | 85°C                      |
| Dissipation Factor    | 0.05% 1kHz, 0.06% 10kHz   |
| Insulation Resistance | 100 GOhms                 |
| Max dV/dt             | 500 V/us                  |
| Inductance            | 6 nH                      |