

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - TE Connectivity ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	E1	REVISED PER ECR-17-008392	29JUN2017	BW	KR

1. ACCEPTS MATE-N-LOK™ SOCKET 350217.
2. SOCKETS PROTRUDE 0.20 MAX AT MATING END; RECESSED 3.90 MIN. AT BACK END.
3. CAUTION: THIS CONNECTOR IS NOT POLARIZED. IT HAS BEEN DESIGNED IN ACCORDANCE WITH THE INTERNATIONAL ORGANIZATION FOR STANDARDIZATION DESIGN DEPICTED IN DOCUMENT 5599/III DATED 4-27-77 UNDER RESOLUTION 59 OF ISO/TC 131/SC5/WG 3. INTENDED USE IS AS SHOWN IN FIGURE 1-1.
4. VISUAL POLARIZING FEATURE.
5. DIMENSIONS SHOWN REPRESENT PRODUCT IN DRY, AS MOLDED, CONDITION. ADDITIONAL 2% GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR.

FIGURE 1 - 1

THIS HOUSING TO BE INSTALLED IN VALVE BODY

SOCKET HOUSING CUT OUT

1-640406-0
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K. WHITAKER 11-24-92			NAME												
DIMENSIONS: mm[INCHES]		CHK R. SWING 11-24-92			VALVE CONNECTOR, SOCKET HOUSING, 5 CIRCUIT, UNIVERSAL MATE-N-LOK™												
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D. SELF 12-11-92	APPLICATION SPEC		RESTRICTED TO												
<table border="1"> <tr><td>0 PLC</td><td>± -</td></tr> <tr><td>1 PLC</td><td>± -</td></tr> <tr><td>2 PLC</td><td>± 0.10</td></tr> <tr><td>3 PLC</td><td>± -</td></tr> <tr><td>4 PLC</td><td>± -</td></tr> <tr><td>ANGLES</td><td>± -</td></tr> </table>		0 PLC	± -	1 PLC	± -	2 PLC	± 0.10	3 PLC	± -	4 PLC	± -	ANGLES	± -	PRODUCT SPEC	SIZE A2	CAGE CODE 00779	DRAWING NO 640406
0 PLC	± -																
1 PLC	± -																
2 PLC	± 0.10																
3 PLC	± -																
4 PLC	± -																
ANGLES	± -																
MATERIAL NYLON UL 94V-2 NATURAL		WEIGHT 0.000000	SCALE 4:1	SHEET 1 of 1	REV E1												
CUSTOMER DRAWING																	

CUSTOMER DRAWING

1471-9 (1/15)

640406