



(1)





NOTES:

MATERIAL: HOUSING: SHELL:			
CONTACT:	STEEL, NICKEI COPPER ALLO		
OPERATING TEMPERATURE:	-55°C ~ 125°C		

ERMOPLASTIC POLYESTER, UL94V-0 EEL, NICKEL PLATED PPER ALLOY, 30µ GOLD PLATED


OPERATING TEMPERATURE:

.XX ±0.13

.XXX ±0.05

10A (CURRENT) **POWER/CO-AX CONTACT RATING:** (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.


INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:



COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY			
		DRAWN: C.B	DATE: JAN. 01/2019		
		CHECKED:	DATE:		
EDA CINC ARE TORONTO, ONTARIO CANADA OR	TORONTO, ONTARIO	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
		DRAWING NUMBER: 630-17W2	2640-1NA	ISSUE	
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-17W2	2640-1NA	1	

5000MΩ min.

1000V AC rms





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

