<u>ــــــــــــــــــــــــــــــــــــ</u>	т п	D	C	A		
A Thread	ØF F F F F F F F F F F F F F F F F F F				4	
ω			LAYOUT SHOWN AS EXAMPLE		3	
	Keying Shown as example					
CHARACTERISTICSStandard : Based on MIL-DTL-38999 Series III	Connector dimensionDimNominalF22.25 Max]				
-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	I22.23 MaxZ31.5 MaxVV THREADM18x1-6g		SOURIAU shall not be liable for any non-cor due to a use of the Products which does the Specifications issued by either of the Parti (professional recommendation, tech	not comply with ies or by a third party		
-Seals & Grommet: Silicon ElastomerN-Contact Plating: Gold over copper Alloy 0.8µm minimum			Country FR	Jurisdiction & Control List Not Listed	2	
-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories			PN: 8D113Z08SE	3		
-Temperature Range <u>:</u> -65°C to +175°C -Salt Spray : 500 hours	A 27-09-2016 First Release					
		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	D	
		TITLE	Aluminium Inline	e plug 8D series		
BASIC SERIES: 8D 1 - 13 Z	08 S B	SCALE	General linear Tolerances:	NPRDS / PROJECT 859		
SHELL TYPE : In line Receptacle CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	ORIEN CONTACT TYPE : SOCKET(50	ITATION : B OO Matings)	U WWW.SOURIAU.COM	This document is the property of SOURIAU it must not be reproduced or communicated without permission	1	
PLATING : Z = Black Zinc Nickel	CONTACT LAYO	DUT : 13-08 FORMAT	SOURIAU DRG 8D113Z08SB-			
H G	F E	D	C B	<u> </u>		

	Т	۵	П	п		0	σ			_
		Contact Layout								
4		$\begin{array}{c} & & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\$								4
_		Contact position ID Contact location X-axis (mm) Y-axis (mm) A +.065 (1.65) +.157 (3.99) B +.170 (4.32) +.000 (0.00) C +.120 (3.05) 120 (3.05) D .000 (0.00) 170 (4.32) E 120 (3.05) 120 (3.05) F 170 (4.32) +.000 (0.00) G 055 (1.65) +.157 (3.99) H +.000 (0.00) +.044 (1.12)								
w	Shell Arrangement size no. 13 -8									3
						SOURIAU shall not be liab due to a use of the Pro	le for any non-conformity ducts which does not com			
						the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
N								ction & Control List Not Listed		2
						PN: 8D113Z08SB				
						First Release				
					ISS DATE Designed By:	Latest modification - by Date:		CUSTOMER DRAWING	MOD N°	-
					TITLE	Alun	ninium Inline plug	8D series		
					SCALE -{	Genera Tolera	ances:	NPRDS / PROJECT 859		-
					SOURIAU			This document is the prope SOURIAU it must not be reproduce communicated without per	d or	_ 1
					FORMAT A3		RIAU DRG N° L13Z08SB-C		SHEET 2/2	
	Н	G	F	E	D	C	B	A		L